



**RNAV SID RWY 22R 1/2**

ADIVO 4N ARVEP 4N IDEPI 4N KOIVU 4N KUVEM 4N NEPEK 4N NUNTO 4N RENKU 4N TEVRU 4N VALOX 4N

DME/DME OPS:	NOT SUPPORTED	CLIMB ALTITUDE:	CLIMB TO 4000 FT OR ASSIGNED ALTITUDE IF LOWER. CLIMB TO A HIGHER LEVEL ONLY WHEN CLEARED BY ATC.
ROUTES:	INITIAL PART OF SID IS CONVENTIONAL. DME REQUIRED. FOR THE CONVENTIONAL PART AND CHANGE-OVER TO RNAV, SEE RNAV PROC CODING TABLES ON THE VERSO OF THE CHART	RADIO CONTACT:	MAINTAIN TWR FREQ UNTIL 1500 FT, THEN CONTACT HELSINKI RADAR FREQ ACCORDING TO RTE.
SQUAWK:	WHEN LINING UP SQUAWK THE ASSIGNED CODE	RNAV RTE	HELSINKI RADAR 119.100
ADDITIONS TO SID:	INSTRUCTIONS CONTAINING DEVIATIONS FROM THE SID (TEMPORARY ALTITUDE RESTRICTIONS ETC) MAY BE INCLUDED IN THE ATC CLEARANCE PRIOR TO TAKE-OFF.	ADIVO 4N, ARVEP 4N, IDEPI 4N, KUVEM 4N, NEPEK 4N, NUNTO 4N, TEVRU 4N	129.850
INITIAL CLIMB:	RWY TRACK UNTIL TURNING DISTANCE AND TURNING ALTITUDE OF AT LEAST 680 FT. PDG 5.0 % (304 FT/NM) UNTIL 4000 FT BASED ON AIRSPACE RESTRICTIONS. CLOSE-IN OBSTACLES EXIST	NOISE ABATEMENT:	AFTER TAKE-OFF CLIMB AS RAPIDLY AS PRACTICABLE TO AT LEAST 2000 FT ABOVE AD ELEV.
		AREA MNM ALT:	SEE AMA INDEX, AIP ENR 6.1 - 3

CHG: radio data

