

WAAS CH 61000 W26B	APP CRS 275°	Rwy Idg TDZE 990 Apt Elev 1026
--	------------------------	--

RNAV (GPS) Y RWY 26R

HARTSFIELD/JACKSON ATLANTA INTL (ATL)

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C (20°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Simultaneous approach authorized with Rwy 27R or 27L or 28, or Rwy 27R and 28. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

MISSED APPROACH:

Climb to 1500 then climbing right turn to 3500 direct TROYS and hold.

D-ATIS ARR 119.65 DEP 125.55	ATLANTA APP CON 127.9 379.9	ATLANTA TOWER 8L-26R 8R-26L 9L-27R 9R-27L 10-28 RWYS 119.1 125.325 123.85 119.3 119.5 254.4					ALL RWYS 121.9	GND CON (8L-26R,8R-26L) (9L-27R,9R-27L) 10-28 121.75 121.65 254.4	ALL RWYS
--	--	--	--	--	--	--	-----------------------------	--	-------------

4 NM
005°
185°
TROYS

MSA RW26R 25 NM
3100

2049
2048
2049
2049
1304
1151
1179
1311
1260
1174

(FAF) AJAAY
2700
275°
(5)

BAMBU
4000
275°
(3.8)

(IF) HAINZ
5000
275°
(6)

(IAF) ZELOW

ELEV 1026	D	TDZE 990
-----------	----------	----------

275°

HIRL all Rwy
TDZ/CL Rwy 8L, 9R, 10, 26R,
27L and 28

RADAR REQUIRED

1500 3500 TROYS

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 69)

HAINZ ZELOW

*LNAV only.

1.3 3.9 NM 5 NM 3.8 NM 6 NM

1.3 3.9 NM 5 NM 3.8 NM 6 NM

CATEGORY	A	B	C	D
LPV DA	1190/18		200 (200-½)	
LNAV/VNAV DA	1426/50		436 (500-1)	
LNAV MDA	1460/24	470 (500-½)	1460/50	470 (500-1)

ATLANTA, GEORGIA
Amdt 4A 12OCT17

HARTSFIELD/JACKSON ATLANTA INTL (ATL)

33°38'N-84°26'W

RNAV (GPS) Y RWY 26R

SE-4, 20 MAR 2025 to 17 APR 2025

SE-4, 20 MAR 2025 to 17 APR 2025