

EDLW AD 2.13 Declared distances

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)
1	2	3	4	5
06 TWY B	2000 1700	2060 1760	2000 1700	1700 NIL
24 TWY C	2000 1700	2060 1760	2000 1700	1700 NIL

Remarks	
6	
06	Nil
24	Nil

EDLW AD 2.14 Approach and runway lighting

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
06	ALSAF LIH 900 m Sequence flash available	G LIH	3.0° 53.00 ft	W LIH	Up to 1100 m: W LIH; 1100 – 1700 m: R/W LIH; 1700 – 2000 m: R LIH. 15 m spacing.	Up to 300 m: R LIH; 300 – 1400 m W LIH; 1400 – 2000 m: Y LIH. 60 m spacing.	R LIH	-
24	ALSAF LIH 900 m Sequence flash available	G LIH	3.0° 53.00 ft	W LIH	Up to 1100 m: W LIH; 1100 – 1700 m: R/W LIH; 1700 – 2000 m: R LIH. 15 m spacing.	Up to 300 m: R LIH; 300 – 1400 m W LIH; 1400 – 2000 m: Y LIH. 60 m spacing.	R LIH	-

Remarks	
10	
06	EFAS ends 300 m prior THR. PAPI located 140 m behind aiming point marking.
24	EFAS ends 300 m prior THR. PAPI located 90 m behind aiming point marking.