


TRANSITION ALTITUDE
8000'

ATIS 126.455
ANDRAVIDA APP 121.125
KEFALLINIA TWR 122.250



MSA 25 NM
KFN VOR/DME

PREVEZA MTMA
FL160/1000FT ABOVE SFC
AKTION APP
FL125/1000 ABOVE SFC

RO TSA
38°52'28"N
020°39'14"E

GART A
38°59'06"N
020°58'06"E

SPOT ELEVATIONS ARE IN FEET
LEVELS INDICATE ALTITUDE AND ARE IN FEET
BEARINGS, TRACKS AND RADIALS ARE MAGNETIC
DISTANCES ARE IN NM
VAR 5°E/2024-Annual Change 6'15"E

ANDRAVIDA MTMA
NORTH SECTOR
UNL/1000FT ABOVE SFC
Class of airspace:
C: FL195-FL660
E: 1000FT ABOVE SFC - FL195

ANDRAVIDA MTMA
SOUTH SECTOR
UNL/1000FT ABOVE SFC
Class of airspace:
C: FL195-FL660
E: 1000FT ABOVE SFC - FL195

KEFALLINIA
TVOR/DME 115.50
KFN 38°06'46.63"N
020°30'16.86"E

ARAXOS
VOR/DME 112.70
ARA 38°09'32.34"N
021°25'45.88"E

Contour
Legend



LGD72A

UNL
8000FT MSL

LGD72B

UNL
8000FT MSL

Change: Replace V61 with V61/Y119, ARA VOR/DME coordinates.

KEFALLINIA / ANNA POLLATOU AIRPORT

**KFN VOR/DME
RWY 32**

Supplementary SIDs : ARA 2T, ROTSA 1T, GARTA 1T

GENERAL:

- When for these SIDs an altitude higher than the transition altitude is designated, then ATC unit shall specify an equivalent flight level.
- For this SIDs a visual climb up to 200 ft is required and then continue with the minimum PDG (Procedure Design Gradient) as described in the following table.

DESIGNATOR	DESCRIPTION	MAX IAS/ BANK ANGLE	MIN CLIMB GRADIENT (PDG)	ALTITUDES
ARA 2T	“Climb on RDL 320 KFN. At RDL 320 KFN / 17 DME. Fix turn right, intercept and follow ARC 19DME KFN. Crossing RDL 055 KFN turn left to join AWY N604 to ARA.”		5.6 % (340 ft / NM) up to FL 160 See Note	Cross RDL 055 KFN at FL 160 or above. SeeNote
ROTSA 1T	“Climb on RDL 320 KFN. At RDL 320 KFN / 17 DME. Fix turn right, intercept and follow ARC 19DME KFN. Crossing RDL 358 KFN turn left, intercept and follow AWY N731 to ROTSA.”		5.6 % (340 ft / NM) up to FL 100 or above	Cross RDL 351 KFN at 8000ft (QNH) or above. Cross RDL 358 KFN at FL 100 or above.
GARTA 1T	“Climb on RDL 320 KFN. At RDL 320 KFN / 17 DME. Fix turn right, intercept and follow ARC 19DME KFN. Crossing RDL 011 KFN turn left, intercept and follow AWY V61/Y119 to GARTA.”		5 % (304 ft / NM) up to FL 100 or above	Cross RDL 351 KFN at 8000ft (QNH) or above. Cross RDL 011 KFN at FL 100 or above.

Note: For departures using AWY N604 as RNAV AWY (with MIN FL 100) a PDG of 5,0% (304 ft/NM) is required with the restriction to cross RDL 055 KFN at FL 100 or above.

PDG	GROUND SPEED	100	120	140	160	180	200
5.0%(304FT/NM)	ROC (FT/Min)	506	608	709	810	911	1013
5.6%(340FT/NM)	ROC(FT/Min)	567	681	794	907	1021	1134