

Type of aid MAG VAR Type of supported OPS VOR/ILS/MLS declination	ID	Frequency/ Channel service provider RPI	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Service volume radius GBAS	Remarks
1	2	3	4	5	6	7	8
Leipzig/Halle							
ILS 08L (CAT III)							
LOC (3° E/2024)	ILNE	108.55 MHz	H24	N 51 26 02.02 E 012 16 21.92		-	Usable: Up to 10 NM in the area 035°(L)/035°(R) in relation to RCL MIN interception altitude: 1620 ft MSL. From 10 NM to 17 NM in the area 035°(L)/ 035°(R) in relation to RCL MIN interception altitude: 2400 ft MSL. From 17 NM to 25 NM in the area 010°(L)/ 010°(R) in relation to RCL MIN interception altitude: 2400 ft MSL.
GP	-	329.75 MHz	H24	N 51 25 58.15 E 012 13 14.34		-	Usable up to 15 NM.
DME	ILNE	CH22y (108.55 MHz *)	H24	N 51 25 58.12 E 012 13 14.34	422	-	* Ghost frequency
Leipzig/Halle							
ILS 08R (CAT III)							
LOC (3° E/2024)	ILSR	111.75 MHz	H24	N 51 24 51.82 E 012 15 51.35		-	Usable: Up to 10.1 NM in the area 035°(L)/035°(R) in relation to RCL MIN interception altitude: 1630 ft MSL. From 10.1 NM to 17 NM in the area 035°(L)/035°(R) in relation to RCL MIN interception altitude: 2400 ft MSL. From 17 NM to 25 NM in the area 010°(L)/ 010°(R) in relation to RCL MIN interception altitude: 2400 ft MSL.
GP	-	333.35 MHz	H24	N 51 24 47.31 E 012 12 30.59		-	Usable up to 15 NM BTN 7°(L) and 8°(R) of RCL.
MM	dot- dash	75.00 MHz	H24	N 51 24 39.90 E 012 11 29.74		-	0.49 NM THR 08R
Leipzig/Halle							
ILS 26L (CAT III)							
LOC (3° E/2024)	ILSL	110.30 MHz	H24	N 51 24 40.43 E 012 11 47.88		-	Usable: Up to 10 NM in the area 035°(L)/035°(R) in relation to RCL MIN interception altitude: 1660 ft MSL. From 10 NM to 17 NM in the area 035°(L)/ 035°(R) in relation to RCL MIN interception altitude: 2500 ft MSL. From 17 NM to 25 NM in the area 010°(L)/ 010°(R) in relation to RCL MIN interception altitude: 2500 ft MSL.
GP	-	335.00 MHz	H24	N 51 24 53.47 E 012 15 03.25		-	Usable up to 15 NM BTN 8°(L) and 8°(R) of RCL.
MM	dot- dash	75.00 MHz	H24	N 51 24 53.03 E 012 16 16.62		-	0.57 NM THR 26L
Leipzig/Halle							
ILS 26R (CAT III)							
LOC (3° E/2024)	ILNW	111.30 MHz	H24	N 51 25 50.32 E 012 12 11.19		-	Usable: Up to 10.2 NM in the area 035°(L)/035°(R) in relation to RCL MIN interception altitude: 1620 ft MSL. From 10.2 NM to 17 NM in the area 035°(L)/035°(R) in relation to RCL MIN interception altitude: 2400 ft MSL. From 17 NM to 25 NM in the area 010°(L)/ 010°(R) in relation to RCL MIN interception altitude: 2400 ft MSL.
GP	-	332.30 MHz	H24	N 51 26 05.10 E 012 15 43.45		-	Usable up to 15 NM BTN 8°(L) and 8°(R) of RCL.
MM	dot- dash	75.00 MHz	H24	N 51 26 02.66 E 012 16 49.86		-	0.49 NM THR 26R