

ENGM RNP S RWY 01R (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	TAVRE	-	-	-4.0	-	-	-	A5000+	K220-	-	-	RNP 1.0
020	TF	GM559	-	-	-4.0	3.9	-	-	A3500+	-	-	-	RNP 1.0
030	RF	GM560	-	-	-4.0	2.4	-	R	-	-	-	GM008 3.900	RNP 0.3
040	RF	GM561	-	-	-4.0	1.8	-	L	A3000+	-	-	GM009 3.400	RNP 0.3
050	TF	GM557	-	-	-4.0	2.6	-	-	A2200+	K205-	-	-	RNP 0.3
060	RF	GM558	-	-	-4.0	1.4	-	R	A1800+	-	-	GM010 3.000	RNP 0.3
070	TF	RW01R	-	-	-4.0	3.4	-	-	-	-	-3.0/50	-	RNP 0.3
080	TF	GM917	Y	-	-4.0	2.7	-	-	-	-	-	-	RNP 1.0
090	DF	NIDIM	Y	-	-4.0	-	-	R	A4000	-	-	-	RNP 1.0
100	DF	GRM	-	-	-4.0	-	-	R	A4000	-	-	-	RNP 1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

RF arc centre coordinates:

RF arc centre identifier	Latitude	Longitude
GM008	600016.92N	0111220.78E
GM009	600246.38N	0105840.55E
GM010	600627.43N	0111020.95E