

Remarks	
14	
06R	Nil
24L	Nil

EDDB AD 2.13 Declared distances

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)
1	2	3	4	5
06L	3600	3660	3600	3300
TWY K1	3300	3360	3300	NIL
TWY K2	2150	2210	2150	NIL
TWY K3	1120	1180	1120	NIL
TWY L2	3500	3560	3500	NIL
TWY L3	2470	2530	2470	NIL
TWY L4	2000	2060	2000	NIL
TWY L6	1190	1250	1190	NIL
24R	3600	3660	3600	3300
TWY K3	2350	2410	2350	NIL
TWY K4	3300	3360	3300	NIL
TWY L5	2065	2125	2065	NIL
TWY L6	2515	2575	2515	NIL
TWY L7	3300	3360	3300	NIL
06R	4000	4060	4000	4000
TWY M3	2475	2535	2475	NIL
TWY M5	2010	2070	2010	NIL
24L	4000	4060	4000	4000
TWY M4	1795	1855	1795	NIL
TWY M6	2265	2325	2265	NIL
TWY M7	2715	2775	2715	NIL

Remarks	
6	
06L	Nil
24R	Nil
06R	Nil
24L	Nil

EDDB AD 2.14 Approach and runway lighting

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
06L	ALSAF LIL_LIH Sequence flash available	G LIH	3.0° 65.00 ft	W LIL_LIH	Up to 2700 m: W LIH; 2700 - 3300 m: R/W LIH; 3300 - 3600 m: R LIH. 15 m spacing	Up to 300 m R LIH; 300 m - 3000 m W LIH; 3000 m - 3600 m Y LIH; 60 m spacing	R LIH	-