

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
26L	ALSAF LIH Sequence flash available	G LIH	3.0° 64.00 ft	W LIH	Up to 2700 m: W LIH; 2700 – 3300 m: R/W LIH; 3300 – RWE: R LIH. 15 m spacing	Up to RWE: W LIH. 60 m spacing.	R LIH	-

Remarks	
10	
08L	LED lights used for RWY approach lighting system, RWY threshold lighting, RWY touch down zone lighting, RWY centre line lights, RWY edge lights, RWY end lighting, RWY guard lights. RETILs: on RWY 08L for TWY A6
26R	LED lights used for RWY approach lighting system, RWY threshold lighting, RWY touch down zone lighting, RWY centre line lights, RWY edge lights, RWY end lighting, RWY guard lights. RETILs: on RWY 26R for TWY A4
08R	RETILs: on RWY 08R for TWY S6
26L	RETILs: on RWY 26L for TWY S3 and S4

EDDP AD 2.15 Other lighting, secondary power supply

1	ABN/IBN location, characteristics and hours of operation	High performance flashing lights white on TWR
2	LDI location and LGT Anemometer location and LGT	See Chart AD 2 EDDP 2-5
3	TWY edge and centre line LGT	TWY edge lights of TWYs A1, A2, A3, A4, A5, A6, A7, A8, A9, H1, H5, H7, H8, S1, S2, S3, S4, S5, S6, S7, S8, S9, S10: B LIL TWY Center line lights of TWYs A1, A2, A3, A4, A5, A6, A7, A8, A9, B, C, E7, E8, G1, H1, H2, H5, H7, H8, K, L, M, N(BTN M-E8), N(BTN W1-M), S1, S2, S3, S4, S5, S6, S7, S8, S9, S10, T, V, W1, Y: G LIH
4	Secondary power supply including switch-over time	Available/0 SEC
5	Remarks	APRON 1: flood light APRON 2: flood light APRON 3: flood light APRON 4: flood light APRON 5: flood light Wind sock lighted at THR 08L/26R and THR 08R/26L

EDDP AD 2.16 Helicopter landing area

1	Coordinates TLOF or THR of FATO Geoid undulation	NIL
2	TLOF and/or FATO elevation m/ft	NIL
3	TLOF and FATO area dimensions, surface type, bearing strength and marking	NIL
4	True BRG of FATO	NIL
5	Declared distance available	NIL
6	APP and FATO lighting	NIL
7	Remarks	NIL