

STANDARD DEPARTURE CHART –
INSTRUMENT (SID) - ICAO

TAIF/Taif Intl (OETF)

RWY 07

BOXID 2C GEVEM 2C MISAM 2C ITLUN 2C

SID RWY 07	
Fix/point	Coordinates
MISAM - RDL 308/38.1 DME TIF	21°54'15"N 040°01'53"E
ITLUN - RDL 025/68.1 DME TIF	22°29'26"N 041°07'21"E
BOXID - RDL 136/51.7 DME TIF	20°49'45"N 041°08'44"E
GEVEM - RDL 228/43.7 DME TIF	21°02'03"N 039°56'05"E
TIF DVORTAC	21°29'11"N 040°32'50"E

ROUTING

SID	TEXT
BOXID 2C	MINIMUM CLIMB GRADIENT OF 4.10 % UNTILL CROSSING 15.0 DME. CLIMB STRAIGHT AHEAD TO ASSIGNED LEVEL, AFTER PASSING 5.0 DME TIF TURN RIGHT (IAS MAX 210 KIAS UNTIL 15.0 DME TIF) TO INTERCEPT AND ESTABLISH THE RDL 136 TIF TO BOXID. CROSSING 23.0 DME TIF AT OR ABOVE 11000 FT.
GEVEM 2C	MINIMUM CLIMB GRADIENT OF 4.10 % UNTILL PASSING 9000 FT. CLIMB STRAIGHT AHEAD TO ASSIGNED LEVEL, AFTER PASSING 5.0 DME TIF TURN RIGHT TO INTERCEPT AND ESTABLISH THE RDL 228 TIF TO GEVEM. CROSS GEVEM AT OR ABOVE 9000 FT.
MISAM 2C	CLIMB STRAIGHT AHEAD TO ASSIGNED LEVEL, AFTER PASSING 5.0 DME TIF TURN LEFT TO INTERCEPT AND ESTABLISH THE RDL 308 TIF TO MISAM. CROSS MISAM AT OR ABOVE 9000 FT.
ITLUN 2C	CLIMB STRAIGHT AHEAD TO ASSIGNED LEVEL, AFTER PASSING 5.0 DME TIF TURN LEFT TO INTERCEPT AND ESTABLISH THE RDL 025 TIF TO ITLUN. CROSS 29.0 DME TIF AT OR ABOVE 11000 FT.

CHANGE: New Table

Amdt:Original 05 SEP 24

ICAO PANS OPS