

Instrument Approach Procedure Coding Tables

Prestwick RNP RWY 20 - Instrument Approach Procedure via ESAUL

Designator	Sequence Number	Path Terminator	Waypoint Name	Fly-over	Course/Track °M (°T)	Turn Direction	Level Constraint	Speed Constraint	Co-ordinates	Remarks and Distance to MAPt
R20R	001	IF	ESAUL	N	-	-	<u>4000</u>	230	554051.11N 0043554.36W	IAF
R20R	002	TF	BITPA	N	115° (113.7°)	RIGHT	<u>2900</u>	200	553850.26N 0042749.55W	IF / 9.5NM
R20R	003	TF	PK20F	N	205° (203.8°)	-	2100	-	553505.65N 0043044.76W	FAF / 5.4NM
R20R	004	TF	RW20	Y	205° (203.8°)	-	-	-	553012.19N 0043432.76W	MAPt
R20R	005	CF	PKM03	N	205° (203.7°)	RIGHT	-	210	552438.95N 0043850.41W	-
R20R	006	TF	TRN	N	220° (218.7°)	-	6000	210	551848.28N 0044701.89W	HOLD

Prestwick RNP RWY 20 - Instrument Approach Procedure via BITPA

Designator	Sequence Number	Path Terminator	Waypoint Name	Fly-over	Course/Track °M (°T)	Turn Direction	Level Constraint	Speed Constraint	Co-ordinates	Remarks and Distance to MAPt
R20C	001	IF	BITPA	N	-	-	<u>2900</u>	200	553850.26N 0042749.55W	IAF / IF / 9.5NM
R20C	002	TF	PK20F	N	205° (203.8°)	-	2100	-	553505.65N 0043044.76W	FAF / 5.4NM
R20C	003	TF	RW20	Y	205° (203.8°)	-	-	-	553012.19N 0043432.76W	MAPt
R20C	004	CF	PKM03	N	205° (203.7°)	RIGHT	-	210	552438.95N 0043850.41W	-
R20C	005	TF	TRN	N	220° (218.7°)	-	6000	210	551848.28N 0044701.89W	HOLD

Prestwick RNP RWY 20 - Instrument Approach Procedure via UTITI

Designator	Sequence Number	Path Terminator	Waypoint Name	Fly-over	Course/Track °M (°T)	Turn Direction	Level Constraint	Speed Constraint	Co-ordinates	Remarks and Distance to MAPt
R20L	001	IF	UTITI	N	-	-	<u>4000</u>	210	553649.01N 0041945.46W	IAF
R20L	002	TF	BITPA	N	296° (293.9°)	LEFT	<u>2900</u>	200	553850.26N 0042749.55W	IF / 9.5NM
R20L	003	TF	PK20F	N	205° (203.8°)	-	2100	-	553505.65N 0043044.76W	FAF / 5.4NM
R20L	004	TF	RW20	Y	205° (203.8°)	-	-	-	553012.19N 0043432.76W	MAPt
R20L	005	CF	PKM03	N	205° (203.7°)	RIGHT	-	210	552438.95N 0043850.41W	-
R20L	006	TF	TRN	N	220° (218.7°)	-	6000	210	551848.28N 0044701.89W	HOLD