

LEIPZIG/HALLE  
RNAV (GPS, DME/DME/IRU) RWY 08R

STANDARD INSTRUMENT DEPARTURE  
ROUTES (SID)

Designator			Route		After Take-Off				Procedure remarks		
					Climb to		Contact				
<b>DRN 2E</b>			<b>Dresden TWO ECHO</b> On course 082° to DP545; to TORPU; to DRN.		FL 70		MUENCHEN RADAR 126.175 when advised by Tower!		-		
Route Type	Path Terminator	Waypoint Identifier	Coordinates	Fly-over	(True Track) MAG Track (°)	Distance (NM)	Turn Direction	Altitude (ft) Flight Level	Speed Limit (kt IAS)	NAV Specification	Remark
Common	CF	DP545	N 51 25 40.94 E 012 33 59.62	N	(T085.7) 082	-	-	-	-	RNAV 1	-
Common	TF	TORPU	N 51 10 14.84 E 013 12 37.89	N	(T122.3) 119	28.8	-	-	-	RNAV 1	-
Common	TF	DRN	N 51 00 55.97 E 013 35 56.00	N	(T122.3) 119	17.4	-	-	-	RNAV 1	-

Designator			Route		After Take-Off				Procedure remarks		
					Climb to		Contact				
<b>GOLAT 1K</b>			<b>GOLAT ONE KILO</b> On course 082° to <u>DP546</u> or 900, whichever is later; RT, direct to DP547, to DP548; to DP540; to GOLAT. MAX IAS 210 KT until crossing DP547.		FL 70		MUENCHEN RADAR 126.175 when advised by Tower!		1. If unable to comply, file GOLAT E. 2. Only available for ACFT with less than 136t MTOW. 3. Only available between 0500 (0400) and 2100 (2000).		
Route Type	Path Terminator	Waypoint Identifier	Coordinates	Fly-over	(True Track) MAG Track (°)	Distance (NM)	Turn Direction	Altitude (ft) Flight Level	Speed Limit (kt IAS)	NAV Specification	Remark
Common	CF	DP546	N 51 24 50.47 E 012 15 22.49	Y	(T085.7) 082	-	-	-	-	RNAV 1	-
Common	CA	-	-	-	(T085.7) 082	-	-	A900+	-	RNAV 1	-
Common	DF	DP547	N 51 21 44.11 E 012 16 58.26	N	-	-	R	-	210-	RNAV 1	-
Common	TF	DP548	N 51 20 14.83 E 012 13 11.38	N	(T237.9) 235	2.8	-	-	-	RNAV 1	-
Common	TF	DP540	N 51 07 29.73 E 012 00 01.51	N	(T213.0) 210	15.2	-	-	-	RNAV 1	-
Common	TF	GOLAT	N 50 54 43.88 E 011 56 16.94	N	(T190.5) 187	13.0	-	-	-	RNAV 1	-

Designator			Route		After Take-Off				Procedure remarks		
					Climb to		Contact				
<b>GOLAT 2E</b>			<b>GOLAT TWO ECHO</b> On course 082° to DP544; to AKASO; to GOLAT.		FL 70		MUENCHEN RADAR 126.175 when advised by Tower!		-		
Route Type	Path Terminator	Waypoint Identifier	Coordinates	Fly-over	(True Track) MAG Track (°)	Distance (NM)	Turn Direction	Altitude (ft) Flight Level	Speed Limit (kt IAS)	NAV Specification	Remark
Common	CF	DP544	N 51 25 37.83 E 012 32 48.98	N	(T085.7) 082	-	-	-	-	RNAV 1	-
Common	TF	AKASO	N 51 08 30.05 E 012 34 43.96	N	(T176.0) 173	17.2	-	-	-	RNAV 1	-
Common	TF	GOLAT	N 50 54 43.88 E 011 56 16.94	N	(T240.7) 237	27.9	-	-	-	RNAV 1	-

Designator			Route		After Take-Off				Procedure remarks		
					Climb to		Contact				
<b>NEVKO 1K</b>			<b>NEVKO ONE KILO</b> On course 082° to <u>DP546</u> or 900, whichever is later; RT, direct to DP547, to DP548; to DP540; to NEVKO. MAX IAS 210 KT until crossing DP547.		FL 70		MUENCHEN RADAR 126.175 when advised by Tower!		1. If unable to comply, file NEVKO E. 2. Only available for ACFT with less than 136t MTOW. 3. Only available between 0500 (0400) and 2100 (2000).		
Route Type	Path Terminator	Waypoint Identifier	Coordinates	Fly-over	(True Track) MAG Track (°)	Distance (NM)	Turn Direction	Altitude (ft) Flight Level	Speed Limit (kt IAS)	NAV Specification	Remark
Common	CF	DP546	N 51 24 50.47 E 012 15 22.49	Y	(T085.7) 082	-	-	-	-	RNAV 1	-
Common	CA	-	-	-	(T085.7) 082	-	-	A900+	-	RNAV 1	-
Common	DF	DP547	N 51 21 44.11 E 012 16 58.26	N	-	-	R	-	210-	RNAV 1	-
Common	TF	DP548	N 51 20 14.83 E 012 13 11.38	N	(T237.9) 235	2.8	-	-	-	RNAV 1	-
Common	TF	DP540	N 51 07 29.73 E 012 00 01.51	N	(T213.0) 210	15.2	-	-	-	RNAV 1	-
Common	TF	NEVKO	N 50 51 27.17 E 011 18 25.93	N	(T238.8) 236	30.8	-	-	-	RNAV 1	-