

**ETMN AD 2.12 Runway Physical Characteristics**

RWY Designator	True BRG	Dimensions of RWY (m)	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
08	078.51°	2440 x 45	RWY PCN 86/F/A/W/T asphalt	53°45.92609'N 008°38.42350'E	THR 68.5 ft TDZ 72.7 ft
26	258.54°	2440 x 45	SWY 26 PCN 90/R/B/W/T concrete	53°46.18782'N 008°40.59904'E	THR 40.8 ft TDZ 63.5 ft

Slope of RWY-SWY	SWY dimensions (m)	CWY dimensions (m)	Strip dimensions (m)	OFZ	Remarks
7	8	9	10	11	12
0.2% / -0.3% / -0.8% 650 m / 850 m / 940 m	Not available	Not available			
0.8% / 0.3% / -0.2% / -0.8% 940 m / 850 m / 650 m / 275	275 x 45	275 x 150	2835 x 300	NIL	NIL

**ETMN AD 2.13 Declared Distances**

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
08	2440	2440	2440	2440	NIL
26	2440	2715	2715	2440	NIL

NORDHOLZ

**ETMN AD 2.14 Approach and Runway Lighting**

RWY Designator	APCH LGT type length INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT length	RWY Centre Line LGT length spacing colour INTST	RWY Edge LGT length spacing colour INTST	RWY End LGT colour WBAR	SWY LGT length colour	Remarks
1	2	3	4	5	6	7	8	9	10
08	NATO-standard White LIH AFLS	Green	PAPI 3.0°	NIL	0-1500m White, 1500m- 2100m Red/ White, 2100m- 2400m Red, 32m LIH	White LIH Distance from RWY edge 2m	Red	Not available	Red lights at OVRN.
26	Modified NATO- standard White LIH AFLS	Green	PAPI 3.0°	NIL	0-1500m white, 1500m- 2100m red/ white, 2100m- 2400m red, 32m LIH	White LIH Distance from RWY edge 2m	Red	Not available	Red lights at OVRN.