

General Remarks	
1.	ATTENTION DEPARTING AIRCRAFT SIMULTANEOUS PARALLEL DEPARTURES IN PROGRESS. PILOTS HAVE TO PROCEED EXACTLY ON EXTENDED CENTERLINE UNTIL STARTING TURNS AS PUBLISHED IN DEPARTURE ROUTES AND SHALL REMAIN ON TWR FREQUENCY UNTIL FURTHER ADVISED.
2.	RWY 08L IS TO BE USED ESPECIALLY FOR DEPARTURES TO NW, N and NE.
3.	PDG 7.2% (435 FT/NM) UNTIL PASSING 1900 DUE TO NOISE ABATEMENT.
4.	1. RNAV-1 or RNP-1 or A-RNP equivalent. 2. GPS required. 3. DME/DME, DME/DME/IRU not authorized.

Designator	Route			After Take-Off				Procedure Remarks/ Procedure Timesheet		
				Climb to		Contact				
ANKER 9Q	ANKER NINE QUEBEC Climb on course 080° to DM070; or 1900, whichever is later; LT, on course 033° to DM077; RT, to DM079; LT, to ANKER (△). MAX IAS 250 kt until ANKER.			FL 070		MUENCHEN RADAR 123.905 WHEN ADVISED BY TOWER!				
Recommen- ded Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	NAV- Specification	Remarks
CF	DM070	N 48 22 07.04 E 011 50 37.92	Y	(T083.4) 080	0.9	-	I -	-	RNAV 1	-
CA	-	-	-	(T083.4) 080	-	-	A1900+	-	RNAV 1	-
CF	DM077	N 48 25 22.59 E 011 55 11.95	-	(T035.6) 033	-	L	-	-	RNAV 1	-
TF	DM079	N 48 27 26.40 E 011 59 51.19	-	(T056.3) 053	3.7	-	-	-	RNAV 1	-
TF	ANKER	N 48 34 21.45 E 012 00 08.38	-	(T001.6) 359	6.9	-	-	250-	RNAV 1	-

Designator	Route			After Take-Off				Procedure Remarks/ Procedure Timesheet		
				Climb to		Contact				
EVIVA 4Q	EVIVA FOUR QUEBEC Climb on course 080° to DM070; or 1900, whichever is later; LT, on course 357° to DM091; LT, to DM089; LT, to EVIVA (△). MAX IAS 250 kt until DM089.			FL 070		MUENCHEN RADAR 123.905 WHEN ADVISED BY TOWER!				
Recommen- ded Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	NAV- Specification	Remarks
CF	DM070	N 48 22 07.04 E 011 50 37.92	Y	(T083.4) 080	0.9	-	-	-	RNAV 1	-
CA	-	-	-	(T083.4) 080	-	-	A1900+	-	RNAV 1	-
CF	DM091	N 48 27 16.58 E 011 52 51.74	-	(T360.0) 357	-	L	-	-	RNAV 1	-
TF	DM089	N 48 34 59.25 E 011 49 40.26	-	(T344.6) 342	8.0	-	-	250-	RNAV 1	-
TF	EVIVA	N 48 40 02.75 E 011 42 10.58	-	(T315.6) 313	7.1	-	-	-	RNAV 1	-

Designator	Route			After Take-Off				Procedure Remarks/ Procedure Timesheet		
				Climb to		Contact				
INPUT 3Q	INPUT THREE QUEBEC Climb on course 080° to <u>DM070</u> ; or 1900, whichever is later; LT, direct to DM073; to DM065; RT, to INPUT (△). MAX IAS 250 kt until DM065.			FL 070		MUENCHEN RADAR 123.905 WHEN ADVISED BY TOWER!				
Recommen- ded Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	NAV- Specification	Remarks
CF	DM070	N 48 22 07.04 E 011 50 37.92	Y	(T083.4) 080	0.9	-	-	-	RNAV 1	-
CA	-	-	-	(T083.4) 080	-	-	A1900+	-	RNAV 1	-
DF	DM073	N 48 25 03.03 E 011 51 59.06	-	-	-	L	-	-	RNAV 1	-
TF	DM065	N 48 34 12.81 E 011 35 51.01	-	(T310.6) 308	14.1	-	-	250-	RNAV 1	-
TF	INPUT	N 48 40 01.57 E 011 32 29.37	-	(T339.0) 336	6.2	-	-	-	RNAV 1	-