

TABULAR DESCRIPTION: RNAV 1 SID RWY 09L (GUNIM 8A, PEXEG 8A, TULNA 8A, VEMBO 8A)

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course/Heading °M(°T)	Turn Direction	Altitude (ft)	Speed Limit (Kt)	Distance/ Time NM/Min	VA °	Navigation Specification
VEMBO 8A										
10	VA			092.34° Mag / 090.51° True		+3400	-250.00		4.00	RNAV 1
20	CF	BL751		062.00° Mag / 060.17° True	L		-250.00			RNAV 1
30	TF	BL701		059.35° Mag / 057.52° True			-250.00	5.95		RNAV 1
40	TF	BL778		038.90° Mag / 037.07° True		-6000		5.73		RNAV 1
50	TF	LIGLO		038.92° Mag / 037.09° True				11.78		RNAV 1
60	TF	VEMBO		088.90° Mag / 087.07° True				42.84		RNAV 1
TULNA 8A										
10	VA			092.34° Mag / 090.51° True		+3400	-250.00		4.00	RNAV 1
20	CF	BL751		062.00° Mag / 060.17° True	L		-250.00			RNAV 1
30	TF	BL753		092.39° Mag / 090.56° True		-6000	-250.00	8.49		RNAV 1
40	TF	BL754		092.41° Mag / 090.58° True			-250.00	3.00		RNAV 1
50	TF	BL756		092.42° Mag / 090.59° True		+7000	-250.00	3.50		RNAV 1
60	TF	TULNA		108.55° Mag / 106.72° True				61.44		RNAV 1
PEXEG 8A										
10	VA			092.34° Mag / 090.51° True		+3400	-250.00		4.00	RNAV 1
20	CF	BL751		062.00° Mag / 060.17° True	L		-250.00			RNAV 1
30	TF	BL753		092.39° Mag / 090.56° True		-6000	-250.00	8.49		RNAV 1
40	TF	BL754		092.41° Mag / 090.58° True			-250.00	3.00		RNAV 1
50	TF	BL756		092.42° Mag / 090.59° True		+7000	-250.00	3.50		RNAV 1
60	TF	BL755		182.43° Mag / 180.60° True	R	-FL080		9.84		RNAV 1
70	TF	BL762		264.11° Mag / 262.28° True	R			10.10		RNAV 1
80	TF	BL404		254.22° Mag / 252.39° True			-FL110	13.00		RNAV 1
90	TF	BL405		272.84° Mag / 271.01° True			-FL110	11.89		RNAV 1
100	TF	BL808		274.18° Mag / 272.35° True			+FL160	26.99		RNAV 1
110	TF	PEXEG		274.07° Mag / 272.24° True				58.69		RNAV 1
GUNIM 8A										
10	VA			092.34° Mag / 090.51° True		+3400	-250.00		4.00	RNAV 1
20	CF	BL751		062.00° Mag / 060.17° True	L		-250.00			RNAV 1
30	TF	BL752		002.17° Mag / 0.34° True			-250.00	3.24		RNAV 1
40	TF	BL780		332.12° Mag / 330.29° True			-FL110	7.07		RNAV 1