

TABULAR DESCRIPTION

RNP RWY 26 (CAT A/B/C)										
Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M (°T)	Distance /Time NM/Min	Turn Direction	Altitude ft	Speed Limit kt	VPA/TCH °/FT	Navigation Specification
10	IF	UD412					+5500.00	-185.00		RNP APCH
20	TF	UD402		171.65° Mag / 171.65° True	4.60		+4400.00	-185.00		RNP APCH
30	TF	UD415		231.65° Mag / 231.65° True	3.50		+4000.00	-185.00		RNP APCH
10	IF	UD413					+5500.00	-185.00		RNP APCH
20	TF	UD401		351.66° Mag / 351.66° True	4.60		+4400.00	-185.00		RNP APCH
30	TF	UD415		291.66° Mag / 291.66° True	3.50		+4000.00	185.00		RNP APCH
10	IF	UD415					+4000.00			RNP APCH
20	TF	UD001		261.63° Mag / 261.63° True	3.50		@3700.00			RNP APCH
30	TF	RW26	Y	261.61° Mag / 261.61° True	6.23		@1715.68		-3.00/50	RNP APCH
10	IF	RW26								RNP APCH
20	CF	UD417	Y	261.56° Mag / 261.56° True				-210.00		RNP APCH
30	DF	UD413				L	+5500.00	-210.00		RNP APCH
40	HM	UD413	Y	351.66° Mag / 351.66° True	1.00 min	L	+5500.00	-230.00		RNP APCH
10	HM	UD415	Y	261.63° Mag / 261.63° True	1.00 min	R	+4000.00	-230.00		RNP APCH

WAYPOINTS LIST

Waypoint	Coordinates
RW26	N 24:37:08.64E 73:54:26.23
UD001	N 24:38:03.55E 74:01:12.13
UD401	N 24:37:16.55E 74:08:34.38
UD402	N 24:40:44.98E 74:08:00.92
UD412	N 24:45:18.92E 74:07:16.91
UD413	N 24:32:42.60E 74:09:18.30
UD415	N 24:38:34.25E 74:05:00.16
UD417	N 24:36:04.82E 73:46:37.36