

Lódz
RNP Rwy 25
ADOXO 2W AGAVA 1W BAXIS 2W
UTOLU 2W VIDEV 2W



STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAOŁódź
RNP RWY 25
ADOXO 2W AGAVA 1W BAXIS 2W UTOLU 2W VIDEV 2W

ADOXO 2W

PDG 9% REQUIRED DUE TO OPERATIONAL REASONS UNTIL LL601, THEREAFTER PDG 5% UNTIL LL604

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	COURSE/TRACK °M (°T)	DISTANCE (NM)	ALTITUDE	SPEED (kt)	NAV SPEC
001	CF	LL601	245 (250.6)	3.97	+2600 ft	-200	RNP 1
002	TF	LL602	335 (340.6)	5.00	-	-220	RNP 1
003	TF	LL536	035 (040.5)	8.58	+6000 ft	-	RNP 1
004	TF	LL604	035 (040.6)	4.96	-FL80	-	RNP 1
005	TF	ADOXO	004 (009.6)	9.72	+FL100	-	RNP 1

AGAVA 1W

PDG 9% REQUIRED UNTIL LL601

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	COURSE/TRACK °M (°T)	DISTANCE (NM)	ALTITUDE	SPEED (kt)	NAV SPEC
001	CF	LL601	245 (250.6)	3.97	+2600 ft	-200	RNP 1
002	TF	LL602	335 (340.6)	5.00	-	-220	RNP 1
003	TF	LL606	065 (070.5)	4.00	+4000 ft	-250	RNP 1
004	TF	LL608	091 (096.5)	8.04	-	-	RNP 1
005	TF	LL618	121 (127.1)	9.71	+6000 ft	-	RNP 1
006	TF	AGAVA	121 (127.3)	9.93	-FL100 +FL80	-	RNP 1

BAXIS 2W

PDG 9% REQUIRED DUE TO OPERATIONAL REASONS UNTIL BAXIS

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	COURSE/TRACK °M (°T)	DISTANCE (NM)	ALTITUDE	SPEED (kt)	NAV SPEC
001	CF	LL601	245 (250.6)	3.97	+2600 ft	-200	RNP 1
002	TF	LL603	303 (309.2)	8.96	+6000 ft	-	RNP 1
003	TF	BAXIS	273 (278.6)	8.32	+FL100	-	RNP 1

UTOLU 2W

PDG 9% REQUIRED DUE TO OPERATIONAL REASONS UNTIL UTOLU

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	COURSE/TRACK °M (°T)	DISTANCE (NM)	ALTITUDE	SPEED (kt)	NAV SPEC
001	CF	LL601	245 (250.6)	3.97	+2600 ft	-200	RNP 1
002	TF	LL603	303 (309.2)	8.96	+6000 ft	-	RNP 1
003	TF	UTOLU	303 (309.0)	10.39	+FL100	-	RNP 1

VIDEV 2W

PDG 9% REQUIRED UNTIL LL601

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	COURSE/TRACK °M (°T)	DISTANCE (NM)	ALTITUDE	SPEED (kt)	NAV SPEC
001	CF	LL601	245 (250.6)	3.97	+2600 ft	-200	RNP 1
002	TF	LL602	335 (340.6)	5.00	-	-220	RNP 1
003	TF	LL606	065 (070.5)	4.00	+4000 ft	-250	RNP 1
004	TF	LL608	091 (096.5)	8.04	-	-	RNP 1
005	TF	LL628	133 (138.9)	8.52	+6000 ft	-	RNP 1
006	TF	VIDEV	149 (155.4)	9.94	+FL100	-	RNP 1

WAYPOINT IDENTIFIER	COORDINATES	
ADOXO	52 06 11.2 N	019 30 26.0 E
AGAVA	51 34 53.1 N	019 57 38.7 E
BAXIS	51 48 31.0 N	018 51 50.0 E
DER25	51 42 57.8 N	019 22 16.9 E
LL536	51 52 51.6 N	019 22 34.6 E
LL601	51 41 38.7 N	019 16 16.0 E
LL602	51 46 21.3 N	019 13 35.2 E
LL603	51 47 17.4 N	019 05 05.0 E
LL604	51 56 37.0 N	019 27 47.8 E
LL606	51 47 41.1 N	019 19 39.6 E
LL608	51 46 45.9 N	019 32 31.7 E
LL618	51 40 54.2 N	019 44 58.4 E
LL628	51 40 21.0 N	019 41 31.0 E
UTOLU	51 53 49.0 N	018 52 03.0 E
VIDEV	51 31 19.4 N	019 48 09.1 E