


CÓRDOBA
RNP Z
RWY 03 (LPV ONLY)



GS		kt	80	100	120	140	160	180
FAP-THR: 4.5 NM		min:s	3:24	2:43	2:16	1:56	1:42	1:31
FAF-MAPT:		min:s						
ROD: 5.2 %		ft/min	425	531	637	743	849	955

ALT/HGT RW03 FNA												
13	12	11	10	9	8	7	6	5	4	3	2	1
									1630 (1340)	1310 (1020)	990 (690)	

CÓRDOBA AD

REQUISITOS DE LA BASE DE DATOS AERONÁUTICA
AERONAUTICAL DATABASE REQUIREMENTS

PROCEDIMIENTOS DE APROXIMACIÓN POR INSTRUMENTOS // INSTRUMENT APPROACH PROCEDURES

RNP Z RWY 03 (LPV ONLY)

COORDENADAS WAYPOINTS // WAYPOINTS COORDINATES											
WPT				COORD							
ALJAQ (IAF)				373726.2N 0045927.9W							
BA05S (FAP)				374606.0N 0045400.8W							
BA08S (IF)				374252.5N 0045615.4W							
BA800				375149.1N 0045001.6W							
BA810				374325.8N 0044430.0W							
BA820				373347.8N 0045112.7W							
RW03 (LTP)				375004.0N 0045115.0W							
Aproximación final de precisión (APV SBAS) - Pendiente (Ángulo de descenso) // Precision final approach (APV SBAS) -Slope (Descent angle)										5.24% (3.00°)	

DME CRÍTICO // CRITICAL DME											
INSTALACIÓN (ID) FACILITY (ID)			FREQ/CH				COORD				
MARTÍN (MAR)			116.20 MHz CH 109X				370319.1N 0045623.6W				

DESCRIPCIÓN TABULAR DEL PROCEDIMIENTO PROCEDURE TABULAR DESCRIPTION											
Número de serie Serial number	Descriptor de trayectoria Path Terminator	Identificador de punto de recorrido Waypoint identifier	Sobrevuelo Fly-over	Curso / Derrota Course/Track °M (°T)	Variación magnética Magnetic variation	Distancia Distance (NM)	Dirección de viraje Turn direction	Altitud Altitude (ft)	Velocidad Speed (kt)	VPA/TCH (°/ft)	Especificación de navegación Navigation specification
ALJAQ (IAF)											
001	IF	ALJAQ	-	-	+0.7	-	-	+5000	-	-	RNP APCH
002	TF	BA08S	-	026 (025.1)	+0.7	6.0	-	+2400	-	-	RNP APCH
003	TF	BA05S	-	030 (028.9)	+0.7	3.7	-	+1800	-	-	RNP APCH
004	TF	RW03	Y	030 (028.9)	+0.7	4.5	-	+341	-	3.0/49	RNP APCH
005	DF	BA800	Y	-	+0.7	-	-	-	-	-	RNP APCH
006	DF	BA810	-	-	+0.7	-	R	-	-185	-	RNP APCH
007	TF	BA820	-	210 (209.0)	+0.7	11.0	-	-	-	-	RNP APCH
008	TF	ALJAQ	-	300 (299.0)	+0.7	7.5	-	+5000	-220	-	RNP APCH

CIRCUITOS DE ESPERA // HOLDING PATTERN											
Descriptor de trayectoria Path Terminator	Identificador de punto de recorrido Waypoint identifier	Sobrevuelo Fly-over	Curso/Derrota Course/Track °M (°T)	Variación magnética Magnetic variation	Distancia/ Tiempo de alejamiento Distance/ Outbound time	Dirección de viraje Turn direction	Altitud MNM/ MNM altitude (ft)	Altitud MAX MAX altitude (ft)	Velocidad Speed (kt)	Especificación de navegación Navigation specification	
HM	ALJAQ (1)	-	028 (027.0)	+0.7	1 MIN	L	5000	-	-	RNAV1	

(1) RNAV1 (DME/DME): MAR DME crítico.
RNAV1 (DME/DME/IRU): Sin DME crítico.

(1) RNAV1 (DME/DME): MAR DME critical.
RNAV1 (DME/DME/IRU): No critical DME.

SBAS LPV FAS DATA BLOCK		
FAS DATA BLOCK		
1	OPERATION MODE	00
2	SERVICE PROVIDER IDENTIFIER	01*
3	AIRPORT IDENTIFIER	LEBA
4	RUNWAY	RW03
5	APPROACH PERFORMANCE DESIGNATOR	0**
6	ROUTE INDICATOR	Z
7	REFERENCE PATH DATA SELECTOR (RPDS)	00
8	REFERENCE PATH IDENTIFIER	E03A***
9	LANDING THRESHOLD POINT (LTP) – LATITUDE	375003.9700N
10	LANDING THRESHOLD POINT (LTP) – LONGITUDE	0045114.9600W
11	LTP HEIGHT ABOVE ELLIPSOID (HAE)	+01389 (138.9m)
12	FLIGHT PATH ALIGNMENT POINT (FPAP) – LATITUDE	375102.1495N
13	FLIGHT PATH ALIGNMENT POINT (FPAP) – LONGITUDE	0045034.3785W
14	THRESHOLD CROSSING HEIGHT (TCH)	0015.00
15	TCH UNIT SELECTOR	1
16	GLIDE PATH ANGLE	03.00
17	COURSE WIDTH AT THRESHOLD	105.00
18	LENGTH OFFSET	0000
19	HORIZONTAL ALERT LIMIT (HAL)	40.0
20	VERTICAL ALERT LIMIT (VAL)	50.0
21	PRECISION APPROACH PATH POINT CRC REMINDER	1EDA8E4D
NON FAS DATA BLOCK		
22	ICAO CODE	LE
23	LTP ORTHOMETRIC HEIGHT	+00888 (0088.8m)
NOTAS // NOTES: *: Este valor "01" identifica a EGNOS como proveedor de servicio. // This value "01" identifies EGNOS as service provider. **: LPV. ***: "E" se refiere a EGNOS. // "E" refers to EGNOS.		

INTENCIONADAMENTE EN BLANCO
INTENTIONALLY BLANK