

**OLBIA / Costa Smeralda****SID RNAV1 RWY 05****REMARK**

Minimum climb gradient 7% (425 FT/NM) until leaving 5000 FT.

Minimum climb gradient 7% (425 FT/NM) until leaving FL85 for SID OLBEK 6K and SUKUN 6K.

Close-in obstacles penetrating OIS 2.5% exist but were not considered for the published Procedure Design Gradient

**ATNET 7K**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	053 (055.4)	3°	-	-	+420	-	RNAV1
DF	EO603	-	-	-	-	-	+3500	-230	RNAV1
TF	ATNET	-	120 (122.7)	-	24.5	-	+FL95	-	RNAV1

**BATOX 6K**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	053 (055.4)	3°	-	-	+420	-	RNAV1
DF	EO603	-	-	-	-	-	+3500	-230	RNAV1
TF	BATOX	-	055 (057.8)	-	25.5	-	+FL95	-	RNAV1

**INDUM 7K**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	053 (055.4)	3°	-	-	+420	-	RNAV1
DF	EO603	-	-	-	-	-	+3500	-230	RNAV1
TF	TUKLU	-	323 (325.7)	-	7.0	L	-	-	RNAV1
TF	EO620	-	303 (305.7)	-	14.7	-	+FL80	-	RNAV1
TF	EO621	-	233 (236.1)	-	7.0	-	-	-	RNAV1
TF	INDUM	-	233 (235.8)	-	19.3	-	+FL95	-	RNAV1

**LABOM 7K**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	053 (055.4)	3°	-	-	+420	-	RNAV1
DF	EO603	-	-	-	-	-	+3500	-230	RNAV1
TF	EO622	-	141 (143.4)	-	12.1	-	+6000	-	RNAV1
TF	VAGVU	-	192 (194.3)	-	14.1	-	-	-	RNAV1
TF	EO623	-	229 (232.1)	-	10.0	-	+FL110	-	RNAV1
TF	LABOM	-	229 (232.0)	-	10.8	-	-	-	RNAV1

**OKIVA 7K**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	053 (055.4)	3°	-	-	+420	-	RNAV1
DF	EO603	-	-	-	-	-	+3500	-230	RNAV1
TF	TUKLU	-	323 (325.7)	-	7.0	L	+5000	-	RNAV1
TF	EO620	-	303 (305.7)	-	14.7	-	+FL80	-	RNAV1
TF	OKIVA	-	300 (302.6)	-	12.1	-	+FL85	-	RNAV1

**OLBEK 6K**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	053 (055.4)	3°	-	-	+420	-	RNAV1
DF	EO603	-	-	-	-	-	+3500	-230	RNAV1
TF	OLBEK	-	023 (025.6)	-	18.2	-	+FL95	-	RNAV1

**SUKUN 6K**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	053 (055.4)	3°	-	-	+420	-	RNAV1
DF	EO603	-	-	-	-	-	+3500	-230	RNAV1
TF	EO622	-	141 (143.4)	-	12.1	-	+6000	-	RNAV1
TF	SUKUN	-	141 (143.4)	-	5.5	-	+FL95	-	RNAV1

**SUTAD 7K**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	053 (055.4)	3°	-	-	+420	-	RNAV1
DF	EO603	-	-	-	-	-	+3500	-230	RNAV1
TF	EO622	-	141 (143.4)	-	12.1	-	+6000	-	RNAV1
TF	VAGVU	-	192 (194.3)	-	14.1	-	-	-	RNAV1
TF	EO623	-	229 (232.1)	-	10.0	-	-	-	RNAV1
TF	EO468	-	271 (273.9)	-	12.6	-	-	-	RNAV1
TF	SUTAD	-	286 (288.4)	-	16.8	-	+FL95	-	RNAV1

**TEREZ 7K**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	053 (055.4)	3°	-	-	+420	-	RNAV1
DF	EO603	-	-	-	-	-	+3500	-230	RNAV1
TF	TUKLU	-	323 (325.7)	-	7.0	L	+5000	-	RNAV1
TF	EO620	-	303 (305.7)	-	14.7	-	+FL80	-	RNAV1
TF	TEREZ	-	293 (296.0)	-	14.8	-	+FL85	-	RNAV1

**WAYPOINT LIST**

Waypoint Identifier	Coordinates
EO468	40°30'26.5" N 009°18'57.2" E
EO603	40°59'07.26" N 009°40'52.1" E
EO620	41°13'28.9" N 009°19'52.7" E
EO621	41°09'34.5" N 009°12'10.7" E
EO622	40°49'26.0" N 009°50'22.9" E
EO623	40°29'34.4" N 009°35'25.1" E