

Notes

1. Attention departing aircraft: Simultaneous parallel departures in progress. Pilots have to proceed exactly on extended centerline until starting turns as published in departure routes and shall remain on TWR frequency until further advised.

Designator	Route			After Take-Off				Remarks Text Page		
				Climb to		Contact				
AKINI 1S	AKINI ONE SIERRA To DM030 on course 261° at or above 1900, RT with 2.5 NM radius to DM031, maximum speed 220 kts, to DM043, RT with 4.1 NM radius to DM044, maximum speed 250 kts, to EMGEP, to AKINI.			FL 70		Muenchen Radar 123.905 When advised by Tower!		1. PDG 7.1% / 431 ft/NM or more until passing 1900 due to operational reasons.		
Recommen- ded Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	NAV- Specification	Remarks
CF	DM030	N 48 20 19.37 E 011 43 32.12	-	(T263.4) 261	1.0	-	A1900+	-	RNP-1/A-RNP RF-Leg required	-
RF	DM031	N 48 22 17.67 E 011 39 26.32	-	-	3.7	R	-	220-		ARC Center: DM032 N 48 22 48.07 E 011 43 06.33 ARC Radius: 2.50 NM
TF	DM043	N 48 26 00.82 E 011 38 18.31	-	(T348.5) 346	3.8	-	-	-		-
RF	DM044	N 48 30 07.32 E 011 40 41.24	-	-	4.7	R	-	250-		ARC Center: DM045 N 48 26 49.52 E 011 44 19.97 ARC Radius: 4.10 NM
TF	EMGEP	N 48 42 00.88 E 012 05 24.96	-	(T053.9) 051	20.4	-	-	-		-
TF	AKINI	N 48 44 59.00 E 012 07 27.00	-	(T024.4) 022	3.3	-	-	250-		-