

**STANDARD ARRIVAL CHART -
INSTRUMENT (STAR) - ICAO**
JEDDAH/King Abdulaziz Intl (OEJN)
RNAV RWY 16R

 BOSUT 2R EGMEG 2R MUVOL 2R ULULU 2R VEMEM 1F MISAM 1F
 MUVOL 1F IMDAP 2R VEMEM 2R MISAM 2R NOMDA 2R NOMDA 1F

TABULAR DESCRIPTION

RNAV RWY 16R											
Serial Number	Path Descriptor	Waypoint Identifier	Fly-Over	Course M°(T°)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/TCH (°/ft)	Navigation Specification
080	TF	JN912	-	336(339.7)	-3.8	6.0	R	-	-	-	RNAV 1
090	TF	JN911	-	066(069.6)	-3.8	6.0	R	@4000	-	-	RNAV 1
100	TF	SOGER	-	156(159.7)	-3.8	6.0	-	@4000	-	-	RNAV 1
110	TF	RESEN	-	156(159.7)	-3.8	6.0	-	@3000	-	-	RNAV 1
IMDAP 2R ARRIVAL											
010	IF	IMDAP	-	-	-	-	-	-	-	-	RNAV 1
020	TF	JN916	-	234(237.6)	-3.8	17.6	-	-8000	@210	-	RNAV 1
030	TF	JN914	-	246(249.9)	-3.8	13.2	R	-6000	-	-	RNAV 1
040	TF	ORSOD	-	336(339.8)	-3.8	11.0	-	@4000	-	-	RNAV 1
050	TF	JN918	-	336(339.7)	-3.8	6.0	-	-	-	-	RNAV 1
060	TF	JN912	-	336(339.7)	-3.8	6.0	R	-	-	-	RNAV 1
070	TF	JN911	-	066(069.6)	-3.8	6.0	R	@4000	-	-	RNAV 1
080	TF	SOGER	-	156(159.7)	-3.8	6.0	-	@4000	-	-	RNAV 1
090	TF	RESEN	-	156(159.7)	-3.8	6.0	-	@3000	-	-	RNAV 1
ULULU 2R ARRIVAL											
010	IF	ULULU	-	-	-	-	-	-	-	-	RNAV 1
020	TF	JN917	-	041(045.2)	-3.8	10.7	-	@8000	@210	-	RNAV 1
030	TF	JN914	-	336(339.6)	-3.8	9.9	-	@8000	-	-	RNAV 1
040	TF	ORSOD	-	336(339.8)	-3.8	11.0	-	@4000	-	-	RNAV 1
050	TF	JN918	-	336(339.7)	-3.8	6.0	-	-	-	-	RNAV 1
060	TF	JN912	-	336(339.7)	-3.8	6.0	R	-	-	-	RNAV 1
070	TF	JN911	-	066(069.6)	-3.8	6.0	R	@4000	-	-	RNAV 1
080	TF	SOGER	-	156(159.7)	-3.8	6.0	-	@4000	-	-	RNAV 1
090	TF	RESEN	-	156(159.7)	-3.8	6.0	-	@3000	-	-	RNAV 1
VEMEM 2R ARRIVAL (Use on ATC instruction only)											
010	IF	VEMEM	-	-	-	-	-	-	-	-	RNAV 1
020	TF	RABTU	-	233(236.8)	-3.8	10.0	L	+13000	@250	-	RNAV 1
030	TF	JN799	-	150(153.6)	-3.8	6.0	-	-	-	-	RNAV 1
040	TF	JN797	-	164(167.4)	-3.8	6.0	-	-	-	-	RNAV 1
050	TF	RABEP	-	177(181.2)	-3.8	6.1	R	+13000	@250	-	RNAV 1
060	TF	IMDAP	-	274(278.2)	-3.8	25.0	-	+10000	-	-	RNAV 1
070	TF	JN916	-	234(237.6)	-3.8	17.6	-	-8000	@210	-	RNAV 1
080	TF	JN914	-	246(249.9)	-3.8	13.2	R	-6000	-	-	RNAV 1
090	TF	ORSOD	-	336(339.8)	-3.8	11.0	-	@4000	-	-	RNAV 1
100	TF	JN918	-	336(339.7)	-3.8	6.0	-	-	-	-	RNAV 1
110	TF	JN912	-	336(339.7)	-3.8	6.0	R	-	-	-	RNAV 1
120	TF	JN911	-	066(069.6)	-3.8	6.0	R	@4000	-	-	RNAV 1
130	TF	SOGER	-	156(159.7)	-3.8	6.0	-	@4000	-	-	RNAV 1
140	TF	RESEN	-	156(159.7)	-3.8	6.0	-	@3000	-	-	RNAV 1
MISAM 2R ARRIVAL (Use on ATC instruction only)											
010	IF	MISAM	-	-	-	-	-	-	-	-	RNAV 1
020	TF	RABEP	-	253(256.7)	-3.8	5.2	R	@11000	@230	-	RNAV 1
030	TF	JN797	-	357(001.2)	-3.8	6.1	-	-	-	-	RNAV 1
040	TF	JN799	-	344(347.4)	-3.8	6.0	-	-	-	-	RNAV 1
050	TF	RABTU	-	330(333.6)	-3.8	6.0	L	@11000	@230	-	RNAV 1
060	TF	IMDAP	-	233(236.7)	-3.8	25.0	-	+10000	-	-	RNAV 1
070	TF	JN916	-	234(237.6)	-3.8	17.6	-	-8000	@210	-	RNAV 1
080	TF	JN914	-	246(249.9)	-3.8	13.2	R	-6000	-	-	RNAV 1
090	TF	ORSOD	-	336(339.8)	-3.8	11.0	-	@4000	-	-	RNAV 1
100	TF	JN918	-	336(339.7)	-3.8	6.0	-	-	-	-	RNAV 1
110	TF	JN912	-	336(339.7)	-3.8	6.0	R	-	-	-	RNAV 1
120	TF	JN911	-	066(069.6)	-3.8	6.0	R	@4000	-	-	RNAV 1
130	TF	SOGER	-	156(159.7)	-3.8	6.0	-	@4000	-	-	RNAV 1
140	TF	RESEN	-	156(159.7)	-3.8	6.0	-	@3000	-	-	RNAV 1
MUVOL 2R ARRIVAL (Use on ATC instruction only)											
010	IF	MUVOL	-	-	-	-	-	-	-	-	RNAV 1
020	TF	ALKEV	-	122(125.4)	-3.8	9.1	R	+13000	@250	-	RNAV 1
030	TF	JN934	-	180(183.8)	-3.8	6.0	-	-	-	-	RNAV 1
040	TF	JN936	-	166(170.0)	-3.8	6.0	-	-	-	-	RNAV 1
050	TF	JN937	-	152(156.2)	-3.8	6.0	L	+13000	@250	-	RNAV 1

CHANGE: Table updated

AMDT: Original, 10 AUG 23

ICAO PANS OPS