

TRANSITION ALTITUDE 6500

CAUTION:
ALL IAS VALUES ARE MAX.

1. Set transponder to 7600.
2. Continue with assigned STAR or on previously assigned heading. Descend to last cleared and acknowledged level.
3. After 3 minutes proceed direct to KAK DVOR/DME and hold. Descent in holding pattern. Execute VOR approach to preferred runway and land.



STANDARD ARRIVAL CHART
INSTRUMENT (STAR) - ICAO

Kraków - Balice
RNAV RWY 25

GOVRI 4G KUKAM 4G LENOV 4G MEBAN 5G MOFKE 2G NETIR 4G PADKA 4G UWLER 2G

GOVRI 4G

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	COURSE / TRACK °M (°T)	DISTANCE (NM)	ALTITUDE	SPEED (kt)	NAV SPEC
001	IF	GOVRI	-	-	-	-	RNAV 1
002	TF	KK546	289 (294.5)	31.55	-	-	RNAV 1
003	TF	KK651	252 (258.0)	9.98	-	-220	RNAV 1
004	TF	KK652	162 (168.2)	5.30	-	-220	RNAV 1
005	TF	KK653	072 (078.2)	5.00	-	-220	RNAV 1
006	TF	KK654	072 (078.2)	5.00	-	-220	RNAV 1
007	TF	KK656	162 (168.2)	5.30	-	-220	RNAV 1
008	TF	BAWZI	252 (258.1)	5.00	+5000 ft	-220	RNAV 1

KUKAM 4G

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	COURSE / TRACK °M (°T)	DISTANCE (NM)	ALTITUDE	SPEED (kt)	NAV SPEC
001	IF	KUKAM	-	-	-	-	RNAV 1
002	TF	KEVJO	176 (181.7)	21.00	-FL090	-	RNAV 1
003	TF	KK651	176 (182.1)	9.85	-	-	RNAV 1
004	TF	KK652	162 (168.2)	5.30	-	-220	RNAV 1
005	TF	KK653	072 (078.2)	5.00	-	-220	RNAV 1
006	TF	KK654	072 (078.2)	5.00	-	-220	RNAV 1
007	TF	KK656	162 (168.2)	5.30	-	-220	RNAV 1
008	TF	BAWZI	252 (258.1)	5.00	+5000 ft	-220	RNAV 1

LENOV 4G

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	COURSE / TRACK °M (°T)	DISTANCE (NM)	ALTITUDE	SPEED (kt)	NAV SPEC
001	IF	LENOV	-	-	-	-	RNAV 1
002	TF	UMTAH	304 (309.7)	22.45	-FL170	-	RNAV 1
003	TF	ENNAW	303 (309.4)	19.52	-	-250	RNAV 1
004	TF	UMJUZ	317 (322.7)	10.52	-FL080	-	RNAV 1
005	TF	KK661	343 (349.3)	5.74	-	-220	RNAV 1
006	TF	KK659	072 (078.2)	5.00	-	-220	RNAV 1
007	TF	KK658	072 (078.2)	5.00	-	-220	RNAV 1
008	TF	BAWZI	342 (348.2)	5.30	+5000 ft	-220	RNAV 1

MEBAN 5G

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	COURSE / TRACK °M (°T)	DISTANCE (NM)	ALTITUDE	SPEED (kt)	NAV SPEC
001	IF	MEBAN	-	-	-	-	RNAV 1
002	TF	DUZOW	041 (046.9)	21.90	-FL110	-	RNAV 1
003	TF	ENNAW	041 (047.0)	6.89	-	-250	RNAV 1
004	TF	UMJUJZ	317 (322.7)	10.52	-FL080	-	RNAV 1
005	TF	KK661	343 (349.3)	5.74	-	-220	RNAV 1
006	TF	KK659	072 (078.2)	5.00	-	-220	RNAV 1
007	TF	KK658	072 (078.2)	5.00	-	-220	RNAV 1
008	TF	BAWZI	342 (348.2)	5.30	+5000 ft	-220	RNAV 1

MOFKE 2G

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	COURSE / TRACK °M (°T)	DISTANCE (NM)	ALTITUDE	SPEED (kt)	NAV SPEC
001	IF	MOFKE	-	-	-	-	RNAV 1
002	TF	KUVJE	087 (092.9)	16.08	-FL210	-	RNAV 1
003	TF	EZLIH	088 (093.5)	10.76	-	-	RNAV 1
004	TF	OTLIC	084 (089.8)	15.41	-	-250	RNAV 1
005	TF	ERHAF	085 (090.6)	20.00	+FL130	-	RNAV 1
006	TF	UXBAF	148 (153.5)	16.93	+FL090	-	RNAV 1
007	TF	NIFHA	148 (153.5)	8.07	-	-	RNAV 1
008	TF	KK652	072 (078.1)	5.00	-	-220	RNAV 1
009	TF	KK653	072 (078.2)	5.00	-	-220	RNAV 1
010	TF	KK654	072 (078.2)	5.00	-	-220	RNAV 1
011	TF	KK656	162 (168.2)	5.30	-	-220	RNAV 1
012	TF	BAWZI	252 (258.1)	5.00	+5000 ft	-220	RNAV 1

NETIR 4G

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	COURSE / TRACK °M (°T)	DISTANCE (NM)	ALTITUDE	SPEED (kt)	NAV SPEC
001	IF	NETIR	-	-	-	-	RNAV 1
002	TF	KK581	008 (013.6)	13.79	-	-	RNAV 1
003	TF	EFLUW	089 (095.0)	9.28	-	-250	RNAV 1
004	TF	KK566	089 (095.2)	9.73	-	-	RNAV 1
005	TF	KK534	061 (066.7)	8.76	-	-	RNAV 1
006	TF	KK536	072 (078.2)	5.00	-	-	RNAV 1
007	TF	KK537	072 (078.2)	5.00	-	-	RNAV 1
008	TF	KK538	072 (078.2)	5.00	-	-	RNAV 1
009	TF	KK661	072 (078.2)	5.00	-	-220	RNAV 1
010	TF	KK659	072 (078.2)	5.00	-	-220	RNAV 1
011	TF	KK658	072 (078.2)	5.00	-	-220	RNAV 1
012	TF	BAWZI	342 (348.2)	5.30	+5000ft	-220	RNAV 1

PADKA 4G

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	COURSE / TRACK °M (°T)	DISTANCE (NM)	ALTITUDE	SPEED (kt)	NAV SPEC
001	IF	PADKA	-	-	-	-	RNAV 1
002	TF	JOSWO	087 (092.9)	13.76	-		RNAV 1
003	TF	KK581	087 (093.0)	6.00	-	-	RNAV 1
004	TF	EFLUW	089 (095.0)	9.28	-	-250	RNAV 1
005	TF	KK566	089 (095.2)	9.73	-	-	RNAV 1
006	TF	KK534	061 (066.7)	8.76	-	-	RNAV 1
007	TF	KK536	072 (078.2)	5.00	-	-	RNAV 1
008	TF	KK537	072 (078.2)	5.00	-	-	RNAV 1
009	TF	KK538	072 (078.2)	5.00	-	-	RNAV 1
010	TF	KK661	072 (078.2)	5.00	-	-220	RNAV 1
011	TF	KK659	072 (078.2)	5.00	-	-220	RNAV 1
012	TF	KK658	072 (078.2)	5.00	-	-220	RNAV 1
013	TF	BAWZI	342 (348.2)	5.30	+5000ft	-220	RNAV 1

UWLER 2G

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	COURSE / TRACK °M (°T)	DISTANCE (NM)	ALTITUDE	SPEED (kt)	NAV SPEC
001	IF	UWLER	-	-	-	-	RNAV 1
002	TF	EZLIH	164 (169.5)	25.77	-	-	RNAV 1
003	TF	OTLIC	084 (089.8)	15.41	-	-250	RNAV 1
004	TF	ERHAF	085 (090.6)	20.00	+FL130	-	RNAV 1
005	TF	UXBAF	148 (153.5)	16.93	+FL090	-	RNAV 1
006	TF	NIFHA	148 (153.5)	8.07	-	-	RNAV 1
007	TF	KK652	072 (078.1)	5.00	-	-220	RNAV 1
008	TF	KK653	072 (078.2)	5.00	-	-220	RNAV 1
009	TF	KK654	072 (078.2)	5.00	-	-220	RNAV 1
010	TF	KK656	162 (168.2)	5.30	-	-220	RNAV 1
011	TF	BAWZI	252 (258.1)	5.00	+5000ft	-220	RNAV 1

WAYPOINT IDENTIFIER	COORDINATES	
BAWZI	50 08 13.7 N	020 13 04.5 E
EFLUW	49 54 16.7 N	019 01 49.6 E
ERHAF	50 33 41.9 N	019 38 40.7 E
ENNAW	49 46 59.9 N	020 11 04.1 E
EZLIH	50 33 48.5 N	018 43 08.4 E
GOVRI	50 06 25.3 N	021 01 54.0 E
DUZOW	49 42 17.9 N	020 03 18.5 E
JOSWO	49 55 22.9 N	018 38 16.0 E
KEVJO	50 27 23.8 N	020 02 38.3 E
KK534	49 56 53.4 N	019 29 15.3 E
KK536	49 57 55.0 N	019 36 49.9 E
KK537	49 58 56.5 N	019 44 24.7 E
KK538	49 59 58.1 N	019 51 59.7 E
KK546	50 19 37.1 N	020 17 18.1 E
KK651	50 17 34.0 N	020 02 03.8 E

NIFHA	50 11 21.5 N	019 56 08.3 E
KK566	49 53 24.6 N	019 16 48.7 E
KK652	50 12 23.1 N	020 03 45.2 E
KK653	50 13 24.6 N	020 11 22.3 E
KK654	50 14 26.2 N	020 18 59.6 E
KK656	50 09 15.3 N	020 20 40.9 E
KK661	50 00 59.6 N	019 59 34.8 E
KK659	50 02 01.2 N	020 07 10.1 E
KK658	50 03 02.7 N	020 14 45.6 E
KK581	49 55 04.6 N	018 47 31.5 E
KUKAM	50 48 22.0 N	020 03 38.0 E
LENOV	49 20 11.0 N	021 00 37.0 E
MEBAN	49 27 18.0 N	019 38 48.0 E
MOFKE	50 35 12.0 N	018 01 06.0 E
NETIR	49 41 40.8 N	018 42 32.4 E
OTLIC	50 33 53.8 N	019 07 18.8 E
KUVJE	50 34 26.4 N	018 26 18.0 E
PADKA	49 56 02.0 N	018 16 59.8 E
UMJUZ	49 55 21.8 N	020 01 13.7 E
UMTAH	49 34 34.4 N	020 34 13.4 E
UWLER	50 59 07.0 N	018 35 41.0 E
UXBAF	50 18 34.0 N	019 50 31.2 E