

BARI / Palese
SID RNAV 1 or RNP1 RWY 25

REMARKS

- 1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation;
- 2) Minimum Climb Gradient: 7.7% (470 FT/NM) for DIVKU 5Z and TOPNO 5Z only;
- 3) Minimum Climb Gradient: 7.0% (425 FT/NM) until reaching FL 120 for PISIP 6Z;
- 4) Minimum Climb Gradient: 7.0% (425 FT/NM) until reaching 5000ft for all other SID.

BANAV 5Z

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	246 (249.5)	4 E	-	-	+594	-	RNAV1/RNP1 (1)
CF	BD609	Y	246 (249.5)	4 E	-	-	+3000	210	RNAV1/RNP1 (1)
DF	BD628	-	-	4 E	-	R	+5000	210	RNAV1/RNP1 (1)
TF	BD631	-	079 (083.3)	-	8.8	-	+ FL 75	-	RNAV1/RNP1 (1)
TF	UVOKA	-	016 (019.8)	-	7.9	-	-	-	RNAV1/RNP1 (1)
TF	PERAV	-	016 (019.8)	-	9.5	-	+ FL 100	-	RNAV1/RNP1 (1)
TF	BANAV	-	012 (015.9)	-	12.5	-	+ FL 100	-	RNAV1/RNP1 (1)

DIVKU 5Z

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	246 (249.5)	4 E	-	-	+594	-	RNAV1/RNP1 (1)
CF	BD609	Y	246 (249.5)	4 E	-	-	+3000	210	RNAV1/RNP1 (1)
TF	BD619	-	246 (249.5)	-	4.7	-	+5000	250	RNAV1/RNP1 (1)
TF	BD621	-	307 (311.2)	-	9.5	-	+FL 100	250	RNAV1/RNP1 (1)
TF	DIVKU	-	307 (311.2)	-	30.3	-	-	-	RNAV1/RNP1 (1)

DOLON 5Z

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	246 (249.5)	4 E	-	-	+594	-	RNAV1/RNP1 (1)
CF	BD609	Y	246 (249.5)	4 E	-	-	+3000	210	RNAV1/RNP1 (1)
DF	BD628	-	-	4 E	-	R	+5000	210	RNAV1/RNP1 (1)
TF	BD631	-	079 (083.3)	-	8.8	-	+ FL 75	-	RNAV1/RNP1 (1)
TF	PIKEL	-	101 (104.8)	-	16.6	-	+FL 100	-	RNAV1/RNP1 (1)
TF	DOLON	-	128 (131.6)	-	26.6	-	+FL 100	-	RNAV1/RNP1 (1)

EKMUR 5Z (ATC discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	246 (249.5)	4 E	-	-	+594	-	RNAV1/RNP1 (1)
CF	BD609	Y	246 (249.5)	4 E	-	-	+3000	210	RNAV1/RNP1 (1)
DF	BD628	-	-	4 E	-	R	+5000	210	RNAV1/RNP1 (1)
TF	EKMUR	-	336 (339.5)	-	11.3	-	+ FL 90	-	RNAV1/RNP1 (1)

FASAN 5Z (ATC discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	246 (249.5)	4 E	-	-	+594	-	RNAV1/RNP1 (1)
CF	BD609	Y	246 (249.5)	4 E	-	-	+3000	210	RNAV1/RNP1 (1)
DF	BD628	-	-	4 E	-	R	+5000	210	RNAV1/RNP1 (1)
TF	BD631	-	079 (083.3)	-	8.8	-	+ FL 75	-	RNAV1/RNP1 (1)
TF	PIKEL	-	101 (104.8)	-	16.6	-	+FL 100	-	RNAV1/RNP1 (1)
TF	BD618	-	143 (147.5)	-	11.4	-	-	-	RNAV1/RNP1 (1)
TF	FASAN	-	143 (147.5)	-	11.4	-	+FL 100	-	RNAV1/RNP1 (1)

LUXIL 5Z

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	246 (249.5)	4 E	-	-	+594	-	RNAV1/RNP1 (1)
CF	BD609	Y	246 (249.5)	4 E	-	-	+3000	210	RNAV1/RNP1 (1)
DF	BD628	-	-	4 E	-	R	+5000	210	RNAV1/RNP1 (1)
TF	BD631	-	079 (083.3)	-	8.8	-	+ FL 75	-	RNAV1/RNP1 (1)
TF	PIKEL	-	101 (104.8)	-	16.6	-	+FL 100	-	RNAV1/RNP1 (1)
TF	BD618	-	143 (147.5)	-	11.4	-	-	-	RNAV1/RNP1 (1)
TF	LUXIL	-	234 (237.6)	-	22.8	R	+FL 100	-	RNAV1/RNP1 (1)

PERAV 5Z (ATC discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	246 (249.5)	4 E	-	-	+594	-	RNAV1/RNP1 (1)
CF	BD609	Y	246 (249.5)	4 E	-	-	+3000	210	RNAV1/RNP1 (1)
DF	BD628	-	-	4 E	-	R	+5000	210	RNAV1/RNP1 (1)
TF	BD631	-	079 (083.3)	-	8.8	-	+ FL 75	-	RNAV1/RNP1 (1)
TF	UVOKA	-	016 (019.8)	-	7.9	-	-	-	RNAV1/RNP1 (1)
TF	PERAV	-	016 (019.8)	-	9.5	-	+ FL 100	-	RNAV1/RNP1 (1)

PISIP 6Z

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	246 (249.5)	4 E	-	-	+594	-	RNAV1/RNP1 (1)
CF	BD609	Y	246 (249.5)	4 E	-	-	+3000	210	RNAV1/RNP1 (1)
DF	BD628	-	-	4 E	-	R	+5000	210	RNAV1/RNP1 (1)
TF	PISIP	-	360 (003.8)	-	17.6	-	+FL 120	-	RNAV1/RNP1 (1)

TOPNO 5Z

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	246 (249.5)	4 E	-	-	+594	-	RNAV1/RNP1 (1)
CF	BD609	Y	246 (249.5)	4 E	-	-	+3000	-	RNAV1/RNP1 (1)
TF	BD619	-	246 (249.5)	-	4.7	-	+5000	-	RNAV1/RNP1 (1)
TF	TOPNO	-	246 (249.5)	-	19.1	-	+ FL 110	-	RNAV1/RNP1 (1)

VURKE 5Z

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	246 (249.5)	4 E	-	-	+594	-	RNAV1/RNP1 (1)
CF	BD609	Y	246 (249.5)	4 E	-	-	+3000	210	RNAV1/RNP1 (1)
DF	BD628	-	-	4 E	-	R	+5000	210	RNAV1/RNP1 (1)
TF	BD631	-	079 (083.3)	-	8.8	-	+ FL 75	-	RNAV1/RNP1 (1)
TF	PIKEL	-	101 (104.8)	-	16.6	-	+FL 100	-	RNAV1/RNP1 (1)
TF	VURKE	-	078 (082.3)	-	42.9	-	+FL 100	-	RNAV1/RNP1 (1)

WAYPOINT LIST

Waypoint Identifier	Coordinates
BD609	41° 05' 32.51"N 016° 35' 52.93" E
BD619	41° 03' 53.66"N 016° 30' 06.55" E
BD621	41° 10' 08.99"N 016° 20' 38.43" E
BD618	41° 01' 25.86"N 017° 17' 35.48" E
BD628	41° 14' 17.47"N 016° 36' 38.64" E
BD631	41° 15' 18.94"N 016° 48' 15.01" E