

## TABULAR DESCRIPTION

## RNP Y RWY05 – Instrument Approach Procedure

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation (°)	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA (°)/TCH (m)	Navigation Specification
010	IF	GIPOR	-	-	-	-	-	+4000	-	-	RNAV1/RNP1 (1)
020	TF	RI501	-	042 (046.1)	-	5.5	-	+3000	-	-	RNAV1/RNP1 (1)
030	TF	RI502	-	049 (052.2)	-	6.0	-	+2000	-	-	RNP APCH
040	TF	RI503	Y	049 (052.3)	-	4.1	-	+800 (2)	-	-	RNP APCH
050	-	RWY05	-	049 (052.3)	-	-	-	@124 (3)	-	-3.0/15	RNP APCH
060	CA	-	-	049 (052.3)	3.7 E	-	-	+850	-185	-	RNP APCH
070	VI	-	-	274 (277.3)	-	-	R	-	-185	-	RNAV1/RNP1 (1)
080	CF	RI502	-	229 (232.3)	3.7 E	-	-	-	-185	-	RNAV1/RNP1 (1)
090	TF	RI501	-	229 (232.3)	-	6.0	-	-	-	-	RNAV1/RNP1 (1)
100	TF	GIPOR	-	222 (226.2)	-	5.5	-	+4000	-	-	RNAV1/RNP1 (1)

- (1) For “monitoring and alerting” reasons, RNP1 specification is required in case of radar service unavailability or degradation  
(2) For LNAV only  
(3) THR altitude plus TCH

## Holding RNAV

Path Terminator	Waypoint Identifier	Inbound Course °M(°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Performance
HM	GIPOR	046° (049.9)	3.8	1/-	L	+4000	-	-210	3.7 E	RNAV1

- (1) RNAV system with holding functionality.  
(2) RNAV system without holding functionality.

## WAYPOINT LIST

Waypoint Identifier	Coordinates
RI501	40°29'26.26" N 014°41'36.45" E
RI502	40°33'06.93" N 014°47'49.59" E
RI503	40°35'37.16" N 014°52'04.33" E