

**EDDM AD 2.15 Other lighting, secondary power supply**

1	ABN/IBN location, characteristics and hours of operation	ABN white/white
2	LDI location and LGT Anemometer location and LGT	See Chart AD 2 EDDM 2-5
3	TWY edge and centre line LGT	TWY edge lights of TWYs A1, A2, A3, A4, A5, A6, A8, A9, A10, A12, A13, A14, A15, B1, B2, B3, B4, B6, B7, B8, B10, B11, B12, B13, B14, B15, D1, D4, M, N, N1, N2, N3, N4, R, S, S1, S5, S6, S7, S8, T: B LIL (within the area of high-speed exit taxiways, holdings, taxi bridges for aircraft) TWY Center line lights of TWYs A1, A2, A3, A4, A5, A6, A8, A9, A10, A12, A13, A14, A15, B1, B2, B3, B4, B6, B7, B8, B10, B11, B12, B13, B14, B15: G LIH (Y/G colour-coded for exit) TWY Center line lights of TWYs B12WEST, C1, C3, C4, C5, CENTER2, D1, D2, D3, D4, D5, D6, E1, E2, E3, H2, M, N, N1, N2, N3, N4, R, S, S1, S2, S3, S4, S5, S6, S7, S8, T, W1, W2: G LIH
4	Secondary power supply including switch-over time	Available/0 SEC
5	Remarks	Nil

**EDDM AD 2.16 Helicopter landing area**

1	Coordinates TLOF or THR of FATO Geoid undulation	NIL
2	TLOF and/or FATO elevation m/ft	NIL
3	TLOF and FATO area dimensions, surface type, bearing strength and marking	TLOF Z1, Z2 Surface: CONC Strength: 90/R/A/W/T Markings: WHITE, YELLOW
4	True BRG of FATO	NIL
5	Declared distance available	NIL
6	APP and FATO lighting	NIL
7	Remarks	Helipads closed. Helicopter take-offs and landings on the runways.

**EDDM AD 2.17 ATS airspace**

1	Designation and lateral limits	CTR München
2	Vertical limits	3500 ft MSL
3	Airspace classification	D
4	ATS unit call sign Language(s)	MUENCHEN TOWER English, German
5	Transition altitude	5000 ft MSL
6	Hours of applicability	NIL
7	Remarks	For detailed airspace description see ENR 2.1