

OLBIA / Costa Smeralda**SID RNAV1 RWY 23****REMARK****Minimum climb gradient: 7% (425 FT/NM) until leaving TRL.**

Close-in obstacles penetrating OIS 2.5% exist but were not considered for the published Procedure Design Gradient

ATNET 8Q

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	233 (235.4)	3°	-	-	+437	-	RNAV1
DF	EO630	-	-	-	-	-	+3000	-	RNAV1
TF	EO631	-	233 (235.3)	-	6.1	-	+5000	-	RNAV1
TF	EO634	-	161 (163.7)	-	10.1	-	+FL70	-	RNAV1
TF	UNBID	-	093 (096.0)	-	9.5	-	-	-	RNAV1
TF	EO635	-	058 (060.4)	-	10.2	-	+FL90	-	RNAV1
TF	SUKUN	-	058 (060.5)	-	10.0	-	-	-	RNAV1
TF	ATNET	-	083 (085.2)	-	10.3	-	+FL95	-	RNAV1

BATOX 8Q

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	233 (235.4)	3°	-	-	+437	-	RNAV1
DF	EO630	-	-	-	-	-	+3000	-220	RNAV1
TF	EO633	-	331 (334.0)	-	14.2	R	+6000	-	RNAV1
TF	TUBTU	-	053 (055.4)	-	15.5	-	+FL90	-	RNAV1
TF	BATOX	-	084 (086.3)	-	29.2	-	+FL95	-	RNAV1

INDUM 8Q

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	233 (235.4)	3°	-	-	+437	-	RNAV1
DF	EO630	-	-	-	-	-	+3000	-	RNAV1
TF	EO631	-	233 (235.3)	-	6.1	-	+5000	-	RNAV1
TF	EO632	-	278 (280.5)	-	8.2	-	+FL70	-	RNAV1
TF	EO422	-	315 (317.8)	-	4.8	-	-	-	RNAV1
TF	INDUM	-	315 (317.7)	-	10.8	-	+FL95	-	RNAV1

LABOM 8Q

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	233 (235.4)	3°	-	-	+437	-	RNAV1
DF	EO630	-	-	-	-	-	+3000	-	RNAV1
TF	EO631	-	233 (235.3)	-	6.1	-	+5000	-	RNAV1
TF	EO634	-	161 (163.7)	-	10.1	-	+FL70	-	RNAV1
TF	LABOM	-	161 (163.8)	-	13.6	-	+FL105	-	RNAV1

OKIVA 8Q

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	233 (235.4)	3°	-	-	+437	-	RNAV1
DF	EO630	-	-	-	-	-	+3000	-220	RNAV1
TF	EO633	-	331 (334.0)	-	14.2	R	+6000	-	RNAV1
TF	OKIVA	-	340 (342.4)	-	18.9	-	+FL85	-	RNAV1

OLBEK 8Q

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	233 (235.4)	3°	-	-	+437	-	RNAV1
DF	EO630	-	-	-	-	-	+3000	-220	RNAV1
TF	EO633	-	331 (334.0)	-	14.2	R	+6000	-	RNAV1
TF	TUBTU	-	053 (055.4)	-	15.5	-	+FL90	-	RNAV1
TF	OLBEK	-	070 (073.0)	-	16.2	-	+FL95	-	RNAV1

SUKUN 8Q

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	233 (235.4)	3°	-	-	+437	-	RNAV1
DF	EO630	-	-	-	-	-	+3000	-	RNAV1
TF	EO631	-	233 (235.3)	-	6.1	-	+5000	-	RNAV1
TF	EO634	-	161 (163.7)	-	10.1	-	+FL70	-	RNAV1
TF	UNBID	-	093 (096.0)	-	9.5	-	-	-	RNAV1
TF	EO635	-	058 (060.4)	-	10.2	-	+FL90	-	RNAV1
TF	SUKUN	-	058 (060.5)	-	10.0	-	+FL95	-	RNAV1

SUTAD 8Q

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	233 (235.4)	3°	-	-	+437	-	RNAV1
DF	EO630	-	-	-	-	-	+3000	-	RNAV1
TF	EO631	-	233 (235.3)	-	6.1	-	+5000	-	RNAV1
TF	SUTAD	-	230 (233.0)	-	16.6	-	+FL95	-	RNAV1

TEREZ 8Q

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	233 (235.4)	3°	-	-	+437	-	RNAV1
DF	EO630	-		-	-	-	+3000	-220	RNAV1
TF	EO633	-	331 (334.0)	-	14.2	R	+6000	-	RNAV1
TF	TEREZ	-	331 (333.8)	-	20.1	-	+FL85	-	RNAV1

WAYPOINT LIST

Waypoint Identifier	Coordinates
EO422	40°50'50.2" N 009°00'35.6" E
EO630	40°49'13.7" N 009°22'07.0" E
EO631	40°45'45.4" N 009°15'31.7" E
EO632	40°47'16.2" N 009°04'50.9" E
EO633	41°01'58.0" N 009°13'55.3" E
EO634	40°36'02.6" N 009°19'15.8" E
EO635	40°40'06.0" N 009°43'14.0" E