


DE-ICING PLATFORM	COM				SANDEFJORD, TORP NORWAY
	GND	126.180 MHZ	DE-ICE	121.705 MHZ	
	ATIS	119.080 MHZ			
	TWR	118.655 MHZ			



NOTES - REMARKS

TAXI ROUTE VIA "N1" TO "N" IS NORMALLY USED.
WHEN DE-ICE POSITION "N" IS OCCUPIED BY PRECEEDING
AIRCRAFT, WAIT IN DE-ICE SEQUENCING POSITION "N1"
OR AS INSTRUCTED BY ATC.

TAXI ROUTE VIA "S1 TO "S" IS ONLY USED DURING PERIODS WITH STRONG SOUTHERLY WINDS. WHEN DE-ICE POSITION "S" IS OCCUPIED BY PRECEEDING AIRCRAFT, WAIT IN DE-ICE SEQUENCING POSITION "S1" OR AS INSTRUCTED BY ATC.

WHEN DE-ICING IS COMPLETED, CONTACT TWR FOR TAXI CLEARANCE.

USE OF TWY Y ALONG APRON DEICE IS LIMITED TO ACFT WITH CODE LETTER C OR SMALLER WHEN DE-ICING OF ACFT WITH CODE LETTER C TAKES PLACE.

USE OF TWY Y ALONG APRON DEICE IS LIMITED TO ACFT WITH CODE LETTER B OR SMALLER WHEN DE-ICING OF ACFT WITH CODE LETTER D TAKES PLACE.

