

Type of aid MAG VAR Type of supported OPS VOR/ILS/MLS declination	ID	Frequency/ Channel service provider RPI	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Service volume radius GBAS	Remarks
1	2	3	4	5	6	7	8
Walda DVOR/DME (2° E/2012)	WLD	112.80 MHz CH75x	H24	N 48 34 45.91 E 011 07 45.79	1390	-	Operational coverage sector 045°–135°: 80 NM, FL 500 sector 135°–045°: 60 NM, FL 500 The DVOR may only be used for the radials in the published en-route, approach and departure procedures and is not permitted for area navigation. DME unusable in sector 040°–200°: below 0 – 10 NM 2600 ft MSL 10 – 20 NM 4000 ft MSL 20 – 30 NM 5600 ft MSL 30 – 40 NM 7300 ft MSL 40 – 50 NM 9100 ft MSL 50 – 60 NM 11000 ft MSL DME unusable in sector 045°–135°: below 60 – 70 NM 16000 ft MSL 70 – 80 NM 18600 ft MSL DME unusable in sector 200°–040°: below 0 – 10 NM 3700 ft MSL 10 – 20 NM 6300 ft MSL 20 – 30 NM 8900 ft MSL 30 – 40 NM 11700 ft MSL 40 – 50 NM 14600 ft MSL 50 – 60 NM 17600 ft MSL