

## TABULAR DESCRIPTION

## RNP X RWY 05 CAT A/B/C – Instrument Approach Procedure

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation (°)	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (Kt)	VPA (°) / TCH (m)	Navigation Specification
010	IF	GONGA	-	-	-	-	-	+4000	-210	-	RNAV1
020	TF	UTUVI	-	045° (048.1°)	-	5.0	-	+3000	-180	-	RNAV1
030	TF	NIBTO	-	045° (048.1°)	-	3.9	-	+3000	-	-	RNP APCH
040	TF	RQ501	Y	045° (048.1°)	-	7.6	-	+940 <sup>(1)</sup>	-	-	RNP APCH
-	-	RWY05	-	-	-	-	-	@172 <sub>(2)</sub>	-	-3.0/15.0	-
050	CF	RQ700	-	168° (171.0°)	3.2 E	-	R	-	-160	-	RNAV1
060	TF	RQ434	-	258° (261.0)	-	11.9	R	+4000	-210	-	RNAV1
070	TF	GONGA	-	315° (318.1)	-	6.0	-	+4000	-210	-	RNAV1
080	HM	GONGA	Y	045° (048.1°)	3.2 E	-	R	+4000	-190	-	RNAV1

## REMARKS

- (1) For LNAV only
- (2) THR Altitude plus TCH.

## Holding RNAV

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Performance
HM	GONGA	045° (048.1°)	3.6	- / 4.5	R	+4000	-5000 (3)	-190	3.2 E	RNAV1

## REMARKS

- 1) For RNAV system with Holding functionality;
- 2) For RNAV system without Holding functionality;
- 3) MAX Holding ALT 5000FT. Higher Level ATC discretion.

## WAYPOINT LIST

Waypoint Identifier	Coordinates
RQ501	43°47'31.05" N 011°10'37.74" E
RQ700	43°33'50.11" N 011°15'14.65" E
RQ434	43°31'58.05" N 010°59'08.04" E