

**STANDARD ARRIVAL CHART -  
INSTRUMENT (STAR) - ICAO**

**JEDDAH/King Abdulaziz Intl(OEJN)  
RNAV RWY 34R**

VEMEM 1C MISAM 1C MUVOL 1C NOMDA 1C  
BOSUT 2N EGMEG 2N IMDAP 2N ULULU 2N  
VEMEM 2N MISAM 2N MUVOL 2N NOMDA 2N

**TABULAR DESCRIPTION**

RNAV RWY 34R											
Serial Number	Path Descriptor	Waypoint Identifier	Fly-Over	Course M°(T°)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/TCH (°/ft)	Navigation Specification
<b>MISAM 2N ARRIVAL</b> (Use on ATC instruction only)											
010	IF	MISAM	-	-	-	-	-	-	-	-	RNAV 1
020	TF	RABEP	-	253(256.7)	-3.8	5.2	R	@FL150	@230	-	RNAV 1
030	TF	JN797	-	357(001.2)	-3.8	6.1	-	-	-	-	RNAV 1
040	TF	JN799	-	344(347.4)	-3.8	6.0	-	-	-	-	RNAV 1
050	TF	RABTU	-	330(333.6)	-3.8	6.0	L	@FL150	@230	-	RNAV 1
060	TF	IMDAP	-	233(236.7)	-3.8	25.0	-	@FL150	-	-	RNAV 1
070	TF	OBTUG	-	241(244.5)	-3.8	17.3	L	+9000	@210	-	RNAV 1
080	TF	PUSPO	-	156(159.8)	-3.8	6.0	-	+7000	-	-	RNAV 1
090	TF	ASVAK	-	156(159.8)	-3.8	6.0	-	-	-	-	RNAV 1
100	TF	ITOMA	-	156(159.8)	-3.8	6.0	-	@3000	-	-	RNAV 1
110	TF	JN798	-	156(159.8)	-3.8	6.0	-	-	-	-	RNAV 1
120	TF	JN796	-	156(159.8)	-3.8	6.0	R	-	-	-	RNAV 1
130	TF	OTAPA	-	246(249.8)	-3.8	5.1	R	@3000	-	-	RNAV 1
140	TF	SOLOG	-	336(339.8)	-3.8	6.0	-	@3000	-	-	RNAV 1
150	TF	PAXOS	-	336(339.8)	-3.8	6.0	-	@2100	-	-	RNAV 1
<b>MUVOL 2N ARRIVAL</b> (Use on ATC instruction only)											
010	IF	MUVOL	-	-	-	-	-	-	-	-	RNAV 1
020	TF	ALKEV	-	122(125.4)	-3.8	9.1	-	-	-	-	RNAV 1
030	TF	KAVOD	-	124(127.6)	-3.8	17.3	R	+FL170	@250	-	RNAV 1
040	TF	JN792	-	207(210.6)	-3.8	6.0	-	-	-	-	RNAV 1
050	TF	JN788	-	193(196.8)	-3.8	6.0	-	-	-	-	RNAV 1
060	TF	JN786	-	179(183.1)	-3.8	6.0	L	+FL170	@250	-	RNAV 1
070	TF	GINKU	-	082(086.2)	-3.8	25.0	-	+13000	@210	-	RNAV 1
080	TF	PUSPO	-	098(101.6)	-3.8	15.5	-	+7000	-	-	RNAV 1
090	TF	ASVAK	-	156(159.8)	-3.8	6.0	-	-	-	-	RNAV 1
100	TF	ITOMA	-	156(159.8)	-3.8	6.0	-	@3000	-	-	RNAV 1
110	TF	JN798	-	156(159.8)	-3.8	6.0	-	-	-	-	RNAV 1
120	TF	JN796	-	156(159.8)	-3.8	6.0	R	-	-	-	RNAV 1
130	TF	OTAPA	-	246(249.8)	-3.8	5.1	R	@3000	-	-	RNAV 1
140	TF	SOLOG	-	336(339.8)	-3.8	6.0	-	@3000	-	-	RNAV 1
150	TF	PAXOS	-	336(339.8)	-3.8	6.0	-	@2100	-	-	RNAV 1
<b>NOMDA 2N ARRIVAL</b> (Use on ATC instruction only)											
010	IF	NOMDA	-	-	-	-	-	-	-	-	RNAV 1
020	TF	LOPAV	-	174(178.2)	-3.8	12.1	L	+FL170	@250	-	RNAV 1
030	TF	JN793	-	093(096.6)	-3.8	6.0	-	-	-	-	RNAV 1
040	TF	JN791	-	107(110.4)	-3.8	6.0	-	-	-	-	RNAV 1
050	TF	JN789	-	121(124.4)	-3.8	6.0	R	+FL170	@250	-	RNAV 1
060	TF	NIVGO	-	217(221.3)	-3.8	25.0	-	+FL150	-	-	RNAV 1
070	TF	OBTUG	-	156(159.7)	-3.8	17.7	-	+9000	@210	-	RNAV 1
080	TF	PUSPO	-	156(159.8)	-3.8	6.0	-	+7000	-	-	RNAV 1
090	TF	ASVAK	-	156(159.8)	-3.8	6.0	-	-	-	-	RNAV 1
100	TF	ITOMA	-	156(159.8)	-3.8	6.0	-	@3000	-	-	RNAV 1
110	TF	JN798	-	156(159.8)	-3.8	6.0	-	-	-	-	RNAV 1
120	TF	JN796	-	156(159.8)	-3.8	6.0	R	-	-	-	RNAV 1
130	TF	OTAPA	-	246(249.8)	-3.8	5.1	R	@3000	-	-	RNAV 1
140	TF	SOLOG	-	336(339.8)	-3.8	6.0	-	@3000	-	-	RNAV 1
150	TF	PAXOS	-	336(339.8)	-3.8	6.0	-	@2100	-	-	RNAV 1

Path Descriptor	Fix Identifier	Inbound Course M°(T°)	Magnetic Variation	Leg Distance (NM)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed Limit (kt)	Navigation Performance
HM	ULULU	028(031.7)	-3.8	1.5 min	R	10000 FT	FL170	240	RNAV 1
HM	IMDAP	233(236.3)	-3.8	1.5 min	L	9000 FT	FL170	240	RNAV 1

TRANSITION ROUTING					
Designation	From	To	Course M°(T°)	Distance (NM)	Arrival Route
LOPAV 1N	LOPAV	IMDAP	144(147.4)	40.5	NOMDA 1C NOMDA 2N
KAVOD 1N	KAVOD	ULULU	151(154.9)	40.0	MUVOL 1C MUVOL 2N
IMLER 1N	IMLER	ULULU	307(311.0)	40.3	BOSUT 2N

CHANGE: Tables updated

AMDT: Original, 10 AUG 23

ICAO PANS OPS