



TABULAR DESCRIPTION

ILS-Z RWY06 – Instrument Approach procedure

RNAV to ILS APPROACH TRANSITION FROM OLEVA											
Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/ TCH	Navigation Specification
010	IF	OLEVA	-	-	-	-	-	+4000	-	-	RNAV1/RNP1 (1)
020	TF	RN561	-	051° (055.0°)	-	3.0	-	+3000	-	-	RNAV1/RNP1 (1)
ILS to RNAV MISSED APPROACH TRANSITION											
010	CF	RN564	Y	051° (055.0°)	3.6	4.2	-	-	-185	-	RNAV1/RNP1 (1)
020	DF	RN565	-	-	-	-	L	-	-185	-	RNAV1/RNP1 (1)
030	TF	RN449	-	249° (252.2°)	-	11.8	-	-	-	-	RNAV1/RNP1 (1)
040	TF	RN567	-	239° (242.1°)	-	10.5	-	-	-	-	RNAV1/RNP1 (1)
050	TF	RELPU	-	196° (199.8°)	-	15.5	-	+6000	-200	-	RNAV1/RNP1 (1)
060	HM	RELPU	-	141° (144.7°)	-	4.0	-	+6000	-200		

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM)	Waypoint Distance (NM)/Timing (min)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	OLEVA	051° (055.0°)	3.0	4.2/-	R	4000	-	-185	3.6	RNAV
HM	RELPU	141° (144.7°)	4.0	- / 1	L	6000	-	-200	3.6	RNAV

(1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation

WAYPOINT LIST

Waypoint Identifier	Coordinates
RN561	40°47'18.06" N 014°06'14.47" E
RN564	40°55'18.99" N 014°21'22.30" E
RN565	40°55'30.77" N 014°12'15.25" E
RN449	40°51'53.35" N 013°57'26.17" E
RN567	40°46'56.49" N 013°45'09.90" E

FIX/POINT	Coordinates (WGS84)
FAF	40°48'49.68" N 014°09'06.77" E