

ELEV AD
233
VAR 1°E (2020)

APP	128.880	C
TWR	128.880	C
GMC	121.705	C
ATIS	120.255	C

REUS
LOC Y
RWY 25

REUS AD

REQUISITOS DE LA BASE DE DATOS AERONÁUTICA
AERONAUTICAL DATABASE REQUIREMENTS

PROCEDIMIENTOS DE APROXIMACIÓN POR INSTRUMENTOS // INSTRUMENT APPROACH PROCEDURES

LOC Y RWY 25

PUNTO POINT	LAT	LONG	AZIMUT VERDADERO TRUE BEARING	DISTANCIA DME DME DISTANCE (NM)
DVOR/DME VLA (IAF)	41°20'33.4"N	001°32'52.4"E	—	—
NDB RUS (IAF)	41°08'52.2"N	001°08'46.1"E	—	—
IF	41°13'46.4"N	001°27'04.2"E	068.94° (LOC IRS)	13.00 DME ILS
FAF	41°11'43.9"N	001°19'59.4"E	068.94° (LOC IRS)	07.28 DME ILS
MAPT	41°09'28.9"N	001°12'13.5"E	068.94° (LOC IRS)	01.00 DME ILS
Aproximación final de no precisión - Pendiente (Ángulo de descenso) // Non-precision final approach - Slope (Descent angle)				5.35% (3.06°)