

IAP RNP - Y RWY 22L – MISSED APPROACH via JESSY

Path Terminator	Waypoint Identifier	Fly Over	Track °M(°T)	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (Kt)	VPA/ TCH	Distance From THR	Naigation Specification	Remarks
IF	IVAPE	-				+5000				RNP APCH	
TF	RP702	-	033° (036.9°)	13.4		+5000				RNP APCH	
TF	RP703	-	309° (313.1°)	7.0	L	+3600				RNP APCH	IF
TF	RP704	-	227° (231.0°)	3.7	L	+3600			8.7	RNP APCH	FAF
-	-	-	201° (204.6°)	-	-	+2200	-	-	4.9	RNP APCH	STEPDOWN FIX
-	-	-	201° (204.5°)	-	-	+1650	-	-	3.4	RNP APCH	STEPDOWN FIX
TF	RP706	Y	201° (204.5°)	8.7		+540			0.0	RNP APCH	MAPt
DF	JESSY					+3000				RNP APCH	

MISSED APPROACH DESCRIPTION

Climbing to 3000 ft proceed direct to JESSY holding pattern.

IVAPE HOLDING PATTERN (RNAV)(3)

Path Terminator	Waypoint Identifier	Inbound Track °M(°T)	Leg Distance (min)**	Turn Direction	Altitude Constraint	Speed Limit KIAS	D (NM)(1)	WD (NM)(2)	TYPE
HM	IVAPE	033°(036.6°)	1	R	+5000	200	3.7	4.8	RNAV1

NEW JESSY HOLDING PATTERN (RNAV)

Path Terminator	Waypoint Identifier	Inbound Track °M(°T)	Leg Distance (min)**	Turn Direction	Altitude Constraint	Speed Limit KIAS	D (NM)(1)	WD (NM)(2)	TYPE
HM	JESSY	033°(036.6°)	1	R	+3000	210	3.8	5.0	RNAV1

- (1): For RNAV system with holding functionality.
- (2): For RNAV system without holding functionality.
- (3): IVAPE holding pattern above FL80 partially inside Firenze CTR.

Waypoints IAP RNP - Y RWY 22L – MISSED APPROACH via JESSY

WAYPOINT	LATITUDE	LONGITUDE
IVAPE	N43370558	E010295540
RP702	N43474906	E010410276
RP703	N43523582	E010335936
RP704	N43501423	E010295790
RP706	N43421723	E010245742
JESSY	N43284029	E010105789