

SID RNAV1 RWY 32 CAGLIARI ELMAS (LIEE)

Warning: "Close In" obstacles penetrating OIS 2.5% exist, but they were not considered for the published procedure design gradient.

REMARKS

1. Turn before DER not allowed.
2. Minimum climb gradient 8% (490ft/NM) until FL120 for SID KOVAS 5J.
3. Minimum climb gradient 8% (490ft/NM) until FL75 for SID CAR 5M.

SID KOVAS 5J

Path Terminator	Waypoint Identifier	Fly Over	Track °Mag (°T)	Magnetic Variation (°)	Distance (NM)	Turn Direction	Altitude Constraint	Speed Limit KIAS	Navigation Performance
CA	-	-	315°(318.0°)	3	-	-	+800	-	RNAV 1
DF	EE601	-	-	-	-	R	+6000	210	RNAV 1
TF	KOVAS	-	003°(005.6°)	3	11.3	-	+FL120	-	RNAV 1

SID CAR 5M

Path Terminator	Waypoint Identifier	Fly Over	Track °Mag (°T)	Magnetic Variation (°)	Distance (NM)	Turn Direction	Altitude Constraint	Speed Limit KIAS	Navigation Performance
CA	-	-	315°(318.0°)	3	-	-	+800	-	RNAV 1
DF	JEZOH	-	-	-	-	R	+FL75	210	RNAV 1
TF	NECAW	-	126°(129.3°)	3	5.6	-	+FL85	-	RNAV 1
TF	CAR	-	126°(129.4°)	3	12.7	-	+FL100	-	RNAV 1

Waypoint Table Formatted according ARINC 424 standards SID RNAV1 RWY 32 LIEE

WAYPOINT	LATITUDE	LONGITUDE
KOVAS	N39384400	E009041400
CAR	N39064100	E009302900
EE601	N39273080	E009024813
JEZOH	N39181974	E009121640
NECAW	N39144519	E009175293