

EDLW AD 2.15 Other lighting, secondary power supply

1	ABN/IBN location, characteristics and hours of operation	ABN white/white on TWR
2	LDI location and LGT Anemometer location and LGT	See Chart AD 2 EDLW 2-5
3	TWY edge and centre line LGT	TWY edge lights of TWYs: B LIL TWY Center line lights of TWYs A, C, D, L (E OF L1), M: G LIL
4	Secondary power supply including switch-over time	Available / 0 SEC
5	Remarks	Nil

EDLW AD 2.16 Helicopter landing area

1	Coordinates TLOF or THR of FATO Geoid undulation	NIL
2	TLOF and/or FATO elevation m/ft	NIL
3	TLOF and FATO area dimensions, surface type, bearing strength and marking	NIL
4	True BRG of FATO	NIL
5	Declared distance available	NIL
6	APP and FATO lighting	NIL
7	Remarks	NIL

EDLW AD 2.17 ATS airspace

1	Designation and lateral limits	CTR Dortmund
2	Vertical limits	2500 ft MSL
3	Airspace classification	D
4	ATS unit call sign Language(s)	DORTMUND TOWER English, German
5	Transition altitude	5000 ft MSL
6	Hours of applicability	NIL
7	Remarks	For detailed airspace description see ENR 2.1

EDLW AD 2.18 ATS communication facilities

Service designation	Call sign	Channel/ Frequency (MHZ)	Sat- voice	Logon address	Hours of operation	Remarks
1	2	3	4	5	6	7
		121.500	-	-	H24	Emergency frequencies for all services
ATIS	DORTMUND ATIS	125.130	-	-	0450 (0350) – 2050 (1950)	Designated operational coverage 60 NM, FL 200
APP	LANGEN RADAR	125.225	-	-	H24	
TWR	DORTMUND TOWER	134.180	-	-	0445 (0345) – 2100 (2000) until 2230 (2130) PPR	Designated operational coverage 25 NM, 4000 ft AGL
	DORTMUND GROUND	121.830	-	-	0445 (0345) – 2200 (2100) until 2230 (2130) PPR	