

SID RNAV1 or RNP1 RWY24 - Description**AGNIS 7G**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	GEMMA	-	-	-	-	-	+6000	-	RNAV1/RNP1 (1)
TF	SOR	-	160° (163.8)	-	8.0	-	-	-	RNAV1/RNP1 (1)
TF	AGNIS	-	154° (157.5)	-	50.2	-	+FL110	-	RNAV1/RNP1 (1)

DELER 7G

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	GEMMA	-	-	-	-	-	+6000	-	RNAV1/RNP1 (1)
TF	SOR	-	160° (163.8)	-	8.0	-	-	-	RNAV1/RNP1 (1)
TF	DELER	-	196° (199.4)	-	25.3	-	+FL110	-	RNAV1/RNP1 (1)

EDOPA 7G

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	GEMMA	-	-	-	-	-	+6000	-	RNAV1/RNP1 (1)
TF	RN617	-	217° (221.0)	-	16.5	-	-	-	RNAV1/RNP1 (1)
TF	EDOPA	-	246° (250.0)	-	13.9	-	+FL110	-	RNAV1/RNP1 (1)

GALTI 7G

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	GEMMA	-	-	-	-	-	+6000	-	RNAV1/RNP1 (1)
TF	SOR	-	160° (163.8)	-	8.0	-	-	-	RNAV1/RNP1 (1)
TF	GALTI	-	079° (082.2)	-	26.0	-	+FL110	-	RNAV1/RNP1 (1)

VEXUV 8G

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	GEMMA	-	-	-	-	-	+6000	-	RNAV1/RNP1 (1)
TF	RN617	-	217° (221.0)	-	16.5	-	-	-	RNAV1/RNP1 (1)
TF	EDOPA	-	246° (250.0)	-	13.9	-	+FL110	-250	RNAV1/RNP1 (1)
TF	VEXUV	-	305° (308.8°)	-	27.2	-	-	-	RNAV1/RNP1 (1)

PEVIR 7G

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	GEMMA	-	-	-	-	-	+6000	-	RNAV1/RNP1 (1)
TF	RN617	-	217° (221.0)	-	16.5	-	-	-	RNAV1/RNP1 (1)
TF	PEVIR	-	187° (190.9)	-	13.5	-	+FL110	-	RNAV1/RNP1 (1)

BEDPI 7G

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	GEMMA	-	-	-	-	-	+6000	-	RNAV1/RNP1 (1)
TF	RN605	-	075° (078.8)	-	6.8	-	+8000	-210	RNAV1/RNP1 (1)
TF	BENTO	-	025° (028.1°)	-	22.3	-	+FL120	-	RNAV1/RNP1 (1)
TF	BEDPI	-	019° (022.3)	-	12.3	-	+FL210	-	RNAV1/RNP1 (1)

POLIT 7G

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	GEMMA	-	-	-	-	-	+6000	-	RNAV1/RNP1 (1)
TF	SOR	-	160° (163.8)	-	8.0	-	-	-	RNAV1/RNP1 (1)
TF	POLIT	-	135° (138.9°)	-	34.7	-	+FL110	-	RNAV1/RNP1 (1)

SIPRO 7J

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	GEMMA	-	-	-	-	-	+6000	-	RNAV1/RNP1 (1)
TF	RN605	-	075° (078.8)	-	6.8	-	+8000	-210	RNAV1/RNP1 (1)
TF	VUNHO	-	346° (349.6)	-	12.0	L	+FL110	-	RNAV1/RNP1 (1)
TF	TEA	-	316° (319.7°)	-	28.9	-	+FL130	-	RNAV1/RNP1 (1)
TF	SIPRO	-	301° (304.4°)	-	15.9	-	-	-	RNAV1/RNP1 (1)

ALAXI 7J

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	GEMMA	-	-	-	-	-	+6000	-	RNAV1/RNP1 (1)
TF	RN605	-	075° (078.8)	-	6.8	-	+8000	-210	RNAV1/RNP1 (1)
TF	VUNHO	-	346° (349.6)	-	12.0	L	+FL110	-	RNAV1/RNP1 (1)
TF	TEA	-	316° (319.7°)	-	28.9	-	+FL130	-	RNAV1/RNP1 (1)
TF	ALAXI	-	310° (313.3°)	-	38.5	-	-	-	RNAV1/RNP1 (1)

1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation

WAYPOINT LIST

Waypoint Identifier	Coordinates
RN605	40°43'56.68" N 014°25'54.48" E
RN617	40°30'10.22" N 014°02'59.33" E
RN703	40°58'41.80" N 014°29'13.20" E