

APP CRS	Rwy Idg	8566
071°	TDZE	119
	Apt Elev	128

RNAV (RNP) Z RWY 6L

LOS ANGELES INTL (LAX)

▼

For uncompensated Baro-VNAV systems, procedure NA below 5°C (41°F) or above 54°C (130°F). Simultaneous approach authorized. GPS required. For inop MALSR, increase RNP 0.30 all Cats visibility to RVR 6000.

MALSR

MISSED APPROACH: Climb to 3000 on track 071° to ZANAV and on track 042° to AMTRA and hold.

D-ATIS	SOCAL APP CON	LOS ANGELES TOWER	GND CON	CLNC DEL	CPDLC
ARR 133.8	124.3 363.2	N 133.9 239.3	N 121.65 327.0	120.35	
DEP 135.65	124.5 235.975	S 120.95 379.1	S 121.75 327.0	327.0	
	(225°-044°)	(090°-224°)	W 121.4 327.0		
		(045°-089°)			

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 77).

NATHN

3600

071°

1800

GP 3.00° TCH 55

5.9 NM

5.1 NM

RW06L

3000

↑

tr 071°

ZANAV

AMTRA

tr 042°

GP 3.00° TCH 55

5.9 NM

5.1 NM

RW06L

CATEGORY	A	B	C	D
RNP 0.30 DA		484/40	365 (400-¾)	

AUTHORIZATION REQUIRED

TDZ/CL Rwy 6R, 7L, 24R, and 25L HIRL all Rwy

LOS ANGELES, CALIFORNIA

Amtd 1 10NOV16

33°57'N-118°24'W

LOS ANGELES INTL (LAX)

RNAV (RNP) Z RWY 6L