

**RIMINI / Miramare**  
**STAR RNAV 1/ RNP 1 RWY 12 DESCRIPTION**

**ANC 2F**

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	ANC	-	-	-	-	-	-	-	RNAV1/RNP1 (3)
TF	PR524	-	302 (305.2)	-	18.2	-	+FL120	-	RNAV1/RNP1 (3)
TF	ROGAK	-	301 (304.9)	-	12.0	-	-	-	RNAV1/RNP1 (3)
TF	PR436	-	325 (328.9)	-	15.1	-	+6000	-	RNAV1/RNP1 (3)
TF	PR424	-	304 (307.8)	-	12.0	-	+3000	-210	RNAV1/RNP1 (3)
TF	PR419	-	304 (307.6)	-	3.9	-	-	-210	RNAV1/RNP1 (3)
TF	BAPIL	-	214 (217.6)	-	5.5	L	+3000	-185	RNAV1/RNP1 (3)

**AMLON 2F**

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	AMLON	-	-	-	-	-	-	-	RNAV1/RNP1 (3)
TF	PR428	-	251 (254.8)	-	13.5	-	+6000	-	RNAV1/RNP1 (3)
TF	PR419	-	251 (254.6)	-	6.4	-	-	-210	RNAV1/RNP1 (3)
TF	BAPIL	-	214 (217.6)	-	5.5	-	+3000	-185	RNAV1/RNP1 (3)

**ASDOR 2F**

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	ASDOR	-	-	-	-	-	-	-	RNAV1/RNP1 (3)
TF	PR432	-	004 (007.7)	-	11.0	-	+FL 100	-	RNAV1/RNP1 (3)
TF	PR426	-	317 (320.3)	-	6.0	-	-	-	RNAV1/RNP1 (3)
TF	PR421	-	317 (320.3)	-	6.0	-	+4000	-210	RNAV1/RNP1 (3)
TF	BAPIL	-	047 (050.2)	-	5.5	R	+3000	-185	RNAV1/RNP1 (3)

**BAGNO 2F**

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	BAGNO	-	-	-	-	-	-	-	RNAV1/RNP1 (3)
TF	PR437	-	052 (054.8)	-	7.0	-	+FL110	-	RNAV1/RNP1 (3)
TF	PR427	-	052 (054.9)	-	10.5	-	TRL	-	RNAV1/RNP1 (3)
TF	PR421	-	052 (055.1)	-	6.5	-	+4000	-210	RNAV1/RNP1 (3)
TF	BAPIL	-	047 (050.2)	-	5.5	-	+3000	-185	RNAV1/RNP1 (3)

**HOLDING RNAV 1**

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	BAPIL	128 (131.0)	3.0	-/3.9	L	+3000	-	-185	+3.4	RNAV 1

(1) RNAV system with holding functionality

(2) RNAV system without holding functionality

(3) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation

**WAYPOINT LIST**

Waypoint Identifier	Coordinates
PR419	44°15'05.93"N - 012°25'55.85"E
PR421	44°07'13.22"N - 012°15'23.83"E
PR424	44°12'44.83"N - 012°30'10.58"E
PR426	44°02'36.50"N - 012°20'43.32"E
PR427	44°03'29.73"N - 012°07'59.34"E
PR428	44°16'47.70"N - 012°34'28.42"E
PR432	43°57'59.53"N - 012°26'01.99"E
PR436	44°05'24.39"N - 012°43'21.71"E
PR437	43°57'27.98"N - 011°56'03.88"E
PR524	43°45'38.57"N - 013°07'44.40"E