



APP CRS	Rwy Idg	12000
263°	TDZE	5309
	Apt Elev	5434

RNAV (RNP) Z RWY 26

DENVER INTL (DEN)

RNP AR APCH.	MALSR	MISSED APPROACH: Climb to 6000 then climbing right turn to 10000 direct NIWOT and hold.
Simultaneous approach authorized. For uncompensated Baro-VNAV systems, procedure NA below -23°C or above 54°C. For inop ALS, increase RNP 0.15 all Cats visibility to RVR 4000, and increase RNP 0.30 all Cats visibility to RVR 4500.		

D-ATIS 125.6 379.9 (ARR) 134.025 (DEP)	DENVER APP CON 119.3 307.3 (N) 120.35 379.3 (S)	DENVER TOWER 132.35 239.275	GND CON 121.35 379.175 (W) 121.85 377.1 (E)	CLNC DEL 118.75	CPDLC
--	---	--------------------------------	---	--------------------	-------



A 5733				
6000	10000	NIWOT		
VGSi and RNAV glidepath not coincident (VGSi Angle 3.00°/TCH 70°).				
GRASP 7000				
RWY26 263° 7000				
See planview for multiple IF locations.				
GP 3.00° TCH 55				
5.2 NM				
CATEGORY	A	B	C	D
RNP 0.15 DA	5566/24 257 (200-½)			
RNP 0.30 DA	5611/24 302 (200-½)			
AUTHORIZATION REQUIRED				

SW-1, 20 MAR 2025 to 17 APR 2025

SW-1, 20 MAR 2025 to 17 APR 2025