

STAR RNAV 1 description**ALBET 2E**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	ALBET	-	-	-	-	-	-FL130 +FL100	270	RNAV1
TF	PZ768	-	128 (131.8)	-	7.6	-	+FL90	-	RNAV1
TF	PZ760	-	083 (086.2)	-	8.3	-	+FL90	-	RNAV1
TF	PZ755	-	128 (131.5)	-	5.0	-	-FL90 +6000	230	RNAV1
TF	PZ750	-	218 (221.7)	-	5.0	R	-FL90 +6000	230	RNAV1
TF	PZ745	-	218 (221.7)	-	5.0	-	-FL90 +6000	230	RNAV1
TF	PZ740	-	218 (221.7)	-	5.0	-	-FL90 +6000	210	RNAV1
TF	PZ735	-	128 (131.5)	-	5.0	L	+5000	210	RNAV1
TF	PZ730	-	038 (041.6)	-	5.0	L	+5000	210	RNAV1
TF	PZ725	-	038 (041.6)	-	5.0	-	+4000	210	RNAV1
TF	LAREN	-	038 (041.6)	-	8.0	-	+4000	At 210	RNAV1

**BASOG 2E**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	BASOG	-	-	-	-	-	-FL120 +FL100	270	RNAV1
TF	PZ862	-	287 (290.5)	-	10.6	-	+6000	-	RNAV1
TF	PZ855	-	262 (265.7)	-	6.7	-	-FL90 +6000	230	RNAV1
TF	PZ850	-	218 (221.7)	-	5.0	-	-FL90 +6000	230	RNAV1
TF	PZ845	-	218 (221.7)	-	5.0	-	-FL90 +6000	230	RNAV1
TF	PZ840	-	218 (221.7)	-	5.0	-	-FL90 +6000	210	RNAV1
TF	PZ735	-	308 (311.6)	-	5.0	R	+5000	210	RNAV1
TF	PZ730	-	038 (041.6)	-	5.0	R	+5000	210	RNAV1
TF	PZ725	-	038 (041.6)	-	5.0	-	+4000	210	RNAV1
TF	LAREN	-	038 (041.6)	-	8.0	-	+4000	At 210	RNAV1

OTGIG 2E

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	OTGIG	-	-	-	-	-	-FL110 +FL90	270	RNAV1
TF	PZ655	-	353 (356.2)	-	4.0	-	+6000	230	RNAV1
TF	PZ850	-	308 (311.7)	-	5.0	-	-FL90 +6000	230	RNAV1
TF	PZ845	-	218 (221.7)	-	5.0	L	-FL90 +6000	230	RNAV1
TF	PZ840	-	218 (221.7)	-	5.0	-	-FL90 +6000	210	RNAV1
TF	PZ735	-	308 (311.6)	-	5.0	R	+5000	210	RNAV1
TF	PZ730	-	038 (041.6)	-	5.0	R	+5000	210	RNAV1
TF	PZ725	-	038 (041.6)	-	5.0	-	+4000	210	RNAV1
TF	LAREN	-	038 (041.6)	-	8.0	-	+4000	At 210	RNAV1

**Holding RNAV**

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	ALBET	158 (161.5)	5.0	-/6.5	R	FL110	FL 150	210	3	RNAV1
HM	OTGIG	016 (019.7)	5.0	-/6.4	L	FL90	FL 110(3)	-	3	RNAV1
HM	BASOG	244 (247.8)	5.0	-/6.5	L	FL100	FL 150	-	3	RNAV1
HM	LAREN	038 (041.6)	3.6	-/4.7	R	4000	-	200	3	RNAV1
HM	ERSAB	031 (034.5)	3.9	-/5.1	R	5000	-	210	3	RNAV1

REMARK

- (1) RNAV system with holding functionality
(2) RNAV system without holding functionality
(3) FL 120 ATC Discretion only

WAYPOINT LIST

Waypoint Identifier	Coordinates
PZ655	45°04'03.6" N 012°06'42.4" E
PZ725	45°10'42.8" N 011°56'10.2" E
PZ730	45°06'58.8" N 011°51'28.6" E
PZ735	45°03'14.5" N 011°46'47.7" E
PZ740	45°06'33.3" N 011°41'30.8" E
PZ745	45°10'17.8" N 011°46'11.7" E
PZ750	45°14'02.1" N 011°50'53.2" E
PZ755	45°17'46.2" N 011°55'35.3" E
PZ760	45°21'05.4" N 011°50'17.6" E
PZ768	45°20'33.1" N 011°38'32.4" E
PZ840	44°59'55.4" N 011°52'03.9" E
PZ845	45°03'39.5" N 011°56'44.9" E
PZ850	45°07'23.3" N 012°01'26.6" E
PZ855	45°11'07.0" N 012°06'08.9" E
PZ862	45°11'37.3" N 012°15'36.6" E