

Type of aid MAG VAR Type of supported OPS VOR/ILS/MLS declination	ID	Frequency/ Channel service provider RPI	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Service volume radius GBAS	Remarks
1	2	3	4	5	6	7	8
Hehlingen DVOR/DME (2° E/2012)	HLZ	117.30 MHz CH120x	H24	N 52 21 48.22 E 010 47 42.79	404	-	Operational coverage sector 0°–360°: 80 NM, 50000 ft MSL The DVOR may only be used for the radials in the published en-route, approach and departure procedures and is not permitted for area navigation. DME unusable in sector 0°–360°: below <hr/> 0 – 10 NM 1700 ft MSL 10 – 20 NM 3100 ft MSL 20 – 30 NM 4700 ft MSL 30 – 40 NM 6400 ft MSL 40 – 50 NM 8300 ft MSL 50 – 60 NM 10200 ft MSL 60 – 70 NM 12400 ft MSL 70 – 80 NM 14600 ft MSL
Leine DVOR/DME (2° E/2012)	DLE	115.20 MHz CH99x	H24	N 52 15 01.15 E 009 53 00.58	395	-	Operational coverage sector 045°–090°: 80 NM, FL 500 sector 090°–045°: 60 NM, FL 500 DVOR/DME unusable in sector 0°–360°: below <hr/> 0 – 10 NM 1400 ft MSL 10 – 20 NM 2700 ft MSL 20 – 30 NM 4100 ft MSL 30 – 40 NM 5600 ft MSL 40 – 50 NM 7300 ft MSL 50 – 60 NM 9100 ft MSL DVOR/DME unusable in sector 045°–090°: below <hr/> 60 – 70 NM 11000 ft MSL 70 – 80 NM 13000 ft MSL In sector 025°–050° the DVOR may only be used for the radials in the published en- route, approach and departure procedures and is not permitted for area navigation.
Nienburg DVOR/DME (4° E/2024)	NIE	109.25 MHz CH29y	H24	N 52 37 33.03 E 009 22 19.74	191	-	Operational coverage sector 0°–360°: 60 NM, 50000 ft MSL The DVOR may only be used for the radials in the published en-route, approach and departure procedures and is not permitted for area navigation. In addition, the DME can be used for the published procedures. DME unusable in sector 0°–240°: below <hr/> 0 – 10 NM 1400 ft MSL 10 – 20 NM 2800 ft MSL 20 – 30 NM 4300 ft MSL 30 – 40 NM 6000 ft MSL 40 – 50 NM 7800 ft MSL 50 – 60 NM 9700 ft MSL DME unusable in sector 240°–360°: below <hr/> 0 – 10 NM 2200 ft MSL 10 – 20 NM 4400 ft MSL 20 – 30 NM 6700 ft MSL 30 – 40 NM 9100 ft MSL 40 – 50 NM 11700 ft MSL 50 – 60 NM 14400 ft MSL