

LAHR  
RWY 03

STANDARD DEPARTURE  
ROUTES – INSTRUMENT  
(SID)

Designator	Route	After Take-Off		Remarks
		Climb to	Contact	
1	2	3	4	5
<b>RWY 03</b>				
<b>NATOR 5Q</b>	<b>NATOR FIVE QUEBEC</b> Climb on course 027° LHR to 7.5 DME LRD; RT, on heading 102° to intercept R282 SUL; on R282 SUL until crossing R194 KRH; RT, on R190 KRH to NATOR (Δ). Climb with 4.6% (280 ft/NM) or more until passing 3800. Climb with 6.4% (390 ft/NM) or more until passing 4000. MAX. IAS 210kt until established on R282 SUL.	FL 70	Strasbourg Approach 119.580	<ol style="list-style-type: none"> <li>1. PDG 4.6% (280 ft/NM) due to obstacles.</li> <li>2. PDG 6.4% (390 ft/NM) due to navaid coverage (SUL).</li> <li>3. During activity of NLFS cross R194 KRH at or above 7500ft (PDG 4.3% (260 ft/NM)). Initial climb altitude is FL80.</li> <li>4. If unable to comply advise ATC prior start-up.</li> </ol>
<b>STR 3Q</b>	<b>STRASBOURG THREE QUEBEC</b> Climb on course 027° LHR to 6.0 DME LRD; LT, on R085 STR to STR (Δ). MAX. IAS 230kt until established inbound STR.			<ol style="list-style-type: none"> <li>1. During glider activities at Neuhof climb with PDG 7.7% (470 ft/NM) or more until passing 5000.</li> <li>2. If unable to comply advise ATC prior start-up</li> </ol>
<b>SUL 6Q</b>	<b>SULZ SIX QUEBEC</b> Climb on course 027° LHR to 7.5 DME LRD; RT, on heading 102° to intercept R282 SUL; on R282 SUL via LUGUS (Δ) to SUL (Δ). Climb with 4.6% (280 ft/NM) or more until passing 3800. Climb with 6.4% (390 ft/NM) or more until passing 4000. MAX. IAS 210kt until established on R282 SUL.			<ol style="list-style-type: none"> <li>1. PDG 4.6% (280 ft/NM) due to obstacles.</li> <li>2. PDG 6.4% (390 ft/NM) due to navaid coverage (SUL).</li> <li>3. If unable to comply advise ATC prior start-up.</li> </ol>

Contact Strasbourg Approach immediately after take-off!