

TABULAR DESCRIPTION

ILS Z RWY35R – Instrument Approach Procedure

RNAV TO ILS APPROACH TRANSITION

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/ TCH	Navigation Specification
010	IF	INLER	-	-	-	-	-	+4000 (1)	@190	-	RNAV 1
020	TF	TODKU	-	349 (351.9)	-	4.0	-	+3000	-180	-	RNAV 1

(1) +3000ft ATC discretion

ILS TO RNAV MISSED APPROACH TRANSITION

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/ TCH	Navigation Specification
010	CF	MC801	Y	346 (349.0)	2.7°E	-	-	-	-200	-	RNAV 1
020	CA	-	-	346 (349.0)	2.7°E	-	-	+1450	-200	-	RNAV 1
030	DF	MC804	-	-	-	-	R	+3500	-200	-	RNAV 1
040	TF	SRN	-	107 (109.8)	-	7.7	-	+4000	-	-	RNAV 1
050	HM	SRN	Y	133 (136.0)	2.7°E	-	R	+4000	-190	-	RNAV 1

HOLDING RNAV

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	INLER	356 (359.0)	3.5	1.0/ -	R	+4000	-	-190	2.7°E	RNAV 1
HM (3)	SRN	133 (136.0)	3.5	1.0/ -	R	+4000 (4)	-	-190 (4)	2.7°E	RNAV 1

(1) RNAV system with holding functionality

(2) RNAV system without holding functionality

(3) Direct entry only

(4) MHA 6000FT (IAS MAX 210 KT)

WAYPOINT LIST

Waypoint Identifier	Coordinates
MC801	45°38'08.77" N 008°43'55.08" E
MC804	45°41'22.61" N 008°50'59.08" E