

SID DESCRIPTION**OKUNO 6A (ATC DISCRETION)**

Over XIBRI turn left until joining RDL 202 RMC VOR (TR 022°) bound to RMC VOR. Leave RMC VOR on RDL 032 (TR 032°) until joining RDL 058 OST VOR (TR 058°) bound to OKUNO.

MCA/MCL: XIBRI 3000 FT; DIBVI 6000 FT; LELSU FL 110

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	XIBRI	Y	-	-	-	-	+3000	-	Conventional/RNAV1
DF	DIBVI	-	-	-	-	L	+6000	-	Conventional/RNAV1
TF	RMC	-	022 (025.0)	-	19.0	-	-	-	Conventional/RNAV1
TF	LELSU	-	032 (035.2)	-	17.1	-	+FL110	-	Conventional/RNAV1
TF	OKUNO	-	058 (061.0)	-	8.4	-	-	-	Conventional/RNAV1

OKUNO 5R

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	XIBRI	-	-	-	-	-	+3000	-	RNAV1
TF	RF622	-	141 (144.0)	-	8.1	-	-	-	RNAV1
TF	DIBVI	-	051 (053.9)	-	7.1	L	+6000	-	RNAV1
TF	RMC	-	022 (025.0)	-	19.0	-	-	-	RNAV1
TF	LELSU	-	032 (035.2)	-	17.1	-	+FL110	-	RNAV1
TF	OKUNO	-	058 (061.0)	-	8.4	-	-	-	RNAV1

OKUNO 9B

Over SOSAK turn left to join RDL 220 RMC VOR (TR 040°) to RMC VOR. Leave RMC VOR on RDL 032 (TR 032°) until joining RDL 058 OST VOR (TR 058°) bound to OKUNO.

MCA/MCL: SOSAK: 3000 FT; EKLOS: 6000 FT; RF532: FL 80; LELSU: FL 110

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	SOSAK	Y	-	-	-	-	+3000	-	Conventional/RNAV1
DF	EKLOS	-	-	-	-	L	+6000	-	Conventional/RNAV1
TF	RF532	-	040 (043.0)	-	5.0	-	+FL80	-	Conventional/RNAV1
TF	RMC	-	040 (043.0)	-	14.0	-	-	-	Conventional/RNAV1
TF	LELSU	-	032 (035.2)	-	17.1	-	+FL110	-	Conventional/RNAV1
TF	OKUNO	-	058 (061.0)	-	8.4	-	-	-	Conventional/RNAV1

OKUNO 7C

Over EKLOS proceed on RDL 220 RMC VOR (TR 040°) bound to RMC VOR. Leave RMC VOR on RDL 032 (TR 032°) until joining RDL 058 OST VOR (TR 058°) bound to OKUNO.

MCL: EKLOS FL 80; LELSU FL 110

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	EKLOS	-	-	-	-	-	+FL80	-	Conventional/ RNAV1
TF	RMC	-	040 (043.0)	-	19.0	-	-	-	Conventional/ RNAV1
TF	LELSU	-	032 (035.2)	-	17.1	-	+FL110	-	Conventional/ RNAV1
TF	OKUNO	-	058 (061.0)	-	8.4	-	-	-	Conventional/ RNAV1

SIPRO 6A (ATC DISCRETION)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	XIBRI	Y	-	-	-	-	+3000	-	RNAV1
DF	DIBVI	-	-	-	-	L	+6000	-	RNAV1
TF	IPMUT	-	022 (024.9)	-	10.1	-	-	-	RNAV1
TF	OTKUB	-	089 (092.6)	-	11.5	-	+FL120	-	RNAV1
TF	FRS	-	090 (093.0)	-	24.0	-	-	-	RNAV1
TF	SIPRO	-	121 (124.1)	-	21.0	-	-	-	RNAV1

SIPRO 5R

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	XIBRI	-	-	-	-	-	+3000	-	RNAV1
TF	RF622	-	141 (144.0)	-	8.1	-	-	-	RNAV1
TF	DIBVI	-	051 (053.9)	-	7.1	L	+6000	-	RNAV1
TF	IPMUT	-	022 (024.9)	-	10.1	-	-	-	RNAV1
TF	OTKUB	-	089 (092.6)	-	11.5	-	+FL120	-	RNAV1
TF	FRS	-	090 (093.0)	-	24.0	-	-	-	RNAV1
TF	SIPRO	-	121 (124.1)	-	21.0	-	-	-	RNAV1

SIPRO 5B

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	SOSAK	Y	-	-	-	-	+3000	-	RNAV1
DF	EKLOS	-	-	-	-	L	+6000	-	RNAV1
TF	RF532	-	040 (043.0)	-	5.0	-	+FL80	-	RNAV1
TF	RF531	-	040 (043.0)	-	3.1	-	-	-	RNAV1
TF	OTKUB	-	089 (092.6)	-	15.2	-	+FL120	-	RNAV1
TF	FRS	-	090 (093.0)	-	24.0	-	-	-	RNAV1
TF	SIPRO	-	121 (124.1)	-	21.0	-	-	-	RNAV1

SIPRO 9C

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	EKLOS	-	-	-	-	-	+FL80	-	RNAV1
TF	RF531	-	040 (043.0)	-	8.1	-	-	-	RNAV1
TF	OTKUB	-	089 (092.6)	-	15.2	-	+FL120	-	RNAV1
TF	FRS	-	090 (093.0)	-	24.0	-	-	-	RNAV1
TF	SIPRO	-	121 (124.1)	-	21.0	-	-	-	RNAV1

TIBER 6A (ATC DISCRETION)

Over XIBRI turn left until joining RDL 202 RMC VOR (TR 022°) bound to RMC VOR. Leave RMC VOR on RDL 358 (TR 358°) bound to TIBER.

MCA/MCL: XIBRI 3000 FT; DIBVI 6000 FT; GEGDU FL110

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	XIBRI	Y	-	-	-	-	+3000	-	Conventional/ RNAV1
DF	DIBVI	-	-	-	-	L	+6000	-	Conventional/ RNAV1
TF	RMC	-	022 (025.0)	-	19.0	-	-	-	Conventional/ RNAV1
TF	GEGDU	-	358 (001.0)	-	13.0	-	+FL110	-	Conventional/ RNAV1
TF	TIBER	-	358 (001.0)	-	13.5	-	-	-	Conventional/ RNAV1

TIBER 9B

Over SOSAK turn left until joining RDL 220 RMC VOR (TR 040°) bound to RMC VOR. Leave RMC VOR on RDL 358 (TR 358°) bound to TIBER.

MCA/MCL: SOSAK: 3000 ft; EKLOS: 6000 ft; RF532: FL 80; GEGDU: FL110

Path Terminator		Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF		SOSAK	Y	-	-	-	-	+3000	-	Conventional/ RNAV1
DF		EKLOS	-	-	-	-	L	+6000	-	Conventional/ RNAV1
TF		RF532	-	040 (043.0)	-	5.0	-	+FL80	-	Conventional/ RNAV1
TF		RMC	-	040 (043.0)	-	14.0	-	-	-	Conventional/ RNAV1
TF		GEGDU	-	358 (001.0)	-	13.0	-	+FL110	-	Conventional/ RNAV1
TF		TIBER	-	358 (001.0)	-	13.5	-	-	-	Conventional/ RNAV1

TIBER 7C

Over EKLOS proceed on RDL 220 RMC VOR (TR 040°) bound to RMC VOR. Leave RMC VOR on RDL 358 (TR 358°) bound to TIBER.

MCL: EKLOS FL 80; GEGDU: FL110

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	EKLOS	-	-	-	-	-	+FL80	-	Conventional/ RNAV1
TF	RMC	-	040 (043.0)	-	19.0	-	-	-	Conventional/ RNAV1
TF	GEGDU	-	358 (001.0)	-	13.0	-	+FL110	-	Conventional/ RNAV1
TF	TIBER	-	358 (001.1)	-	13.5	-	-	-	Conventional/ RNAV1

TIBER 5R

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	XIBRI	-	-	-	-	-	+3000	-	RNAV1
TF	RF622	-	141 (144.0)	-	8.1	-	-	-	RNAV1
TF	DIBVI	-	051 (053.9)	-	7.1	L	+6000	-	RNAV1
TF	RMC	-	022 (025.0)	-	19.0	-	-	-	RNAV1
TF	GEGDU	-	358 (001.0)	-	13.0	-	+FL110	-	RNAV1
TF	TIBER	-	358 (001.0)	-	13.5	-	-	-	RNAV1

WAYPOINT LIST

Waypoint Identifier	Coordinates
RF531	41°40'23.1"N 012°25'24.4"E
RF532	41°38'06.1"N 012°22'33.7"E
RF622	41°26'52.2"N 012°16'59.5"E