

Initial climb description

After take-off proceed on TR 132° until PO606, then join the assigned SID.

Minimum climb gradient:

- 350 ft/NM (5.8%) until passing 4000 ft due to obstacles;
- 500 ft/NM (8.2%) until passing 4000 ft (8.7% until passing FL110 for SID EXFIN 7C) for ATC reasons.

Execute the turn with:

- 20° bank angle
- IAS MAX 220 kt.

WARNING

There are close-in obstacles penetrating OIS 2.5% but they were not considered for the published procedure design gradient.

SID RNAV 1 RWY 14 description

Initial climb procedure executed:

EXFIN 7C

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO606	-	132°	3 E	-	-	+4000	- 220	RNAV1
TF	PO612	-	062°	-	13.2	-	+FL110	- 220	RNAV1
TF	EXFIN	-	062°	-	9.0	-	-	-	RNAV1

EZRAF 6A

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO606	-	132°	3 E	-	-	+4000	- 220	RNAV1
TF	EZRAF	-	099°	-	33.2	-	+FL95	-	RNAV1

FAMXO 6A (ATC discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO606	-	132°	3 E	-	-	+4000	- 220	RNAV1
TF	FAMXO	-	140°	-	40.6	-	+FL130	-	RNAV1

OSBUL 7H

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO606	-	132°	3 E	-	-	+4000	- 220	RNAV1

TF	OSBUL	-	191°	-	-	31.5	+FL90	- 220	RNAV1
----	-------	---	------	---	---	------	-------	-------	-------

OSKOR 7H

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO606	Y	132°	3 E	-	-	+4000	- 220	RNAV1
CF	PO604	-	261°	3 E	-	R	-	- 220	RNAV1
TF	OSKOR	-	007°	-	23.4	R	+FL110	- 220	RNAV1

TAGHE 6A (ATC discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO606	-	132°	3 E	-	-	+4000	- 220	RNAV1
TF	TAGHE	-	119°	-	36.6	-	+FL95	-	RNAV1

UVNIB 1H (ATC discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO606	Y	132°	3 E	-	-	+4000	- 220	RNAV1
CF	PO604	-	261°	3 E	-	R	-	- 220	RNAV1
TF	UVNIB	-	261°	-	20.3	-	+FL90	-	RNAV1

Waypoints table formatted according ARINC 424 standards

Waypoint	Latitude	Longitude
PO604	N45155688	E010005760
PO606	N45195731	E010280344
PO612	N45252423	E010450534