

**TSE DESCRIPTION****ESINO 6V**

Proceed on TR 215° (RDL 215 OST VOR) bound to ESINO (RDL 174/50NM TAQ VOR/DME).

MCA/MCL: OST VOR/DME 5000 FT; ESINO FL 90 (1)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	OST	-	-	-	-	-	+5000	-	Conventional/ RNAV1
TF	TORLI	-	215° (218.5°)	-	16.0	-	-	-	Conventional/ RNAV1
TF	ESINO	-	215° (218.5°)	-	16.0	-	(1)	-	Conventional/ RNAV1

(1) FL90 if proceeding via M126; FL100 if proceeding via Z924 or M738

**GILIO 6V**

Proceed on TR 278° (RDL278 OST VOR) bound to NENIG then turn right and proceed on TR 310° (RDL130 ELB VOR) bound to GILIO.

MCA/MCL: OST VOR/DME 5000FT; GILIO (2)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	OST	-	-	-	-	-	+5000	-	Conventional/ RNAV1
TF	NENIG	-	278° (281.1°)	-	29.5	-	-	-	Conventional/ RNAV1
TF	GILIO	-	310° (313.0°)	-	40.9	-	(2)	-	Conventional/ RNAV1

(2) FL200 for aircraft bound to LIML via Q704/ FL100 for others.

**KONUT 6V**

Proceed on RDL 215 OST VOR bound to TORLI, then turn left on TR 177° bound to KONUT.

MCA/MCL: OST VOR/DME 5000 FT; KONUT FL 100

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	OST	-	-	-	-	-	+5000	-	Conventional/ RNAV1
TF	TORLI	-	215° (218.5°)	-	16.0	-	-	-	Conventional/ RNAV1
TF	KONUT	-	177° (179.3°)	-	18.2	-	+FL100	-	Conventional/ RNAV1

**OKUNO 6S**

Proceed on TR 187° (RDL 187 OST VOR) bound to XIBRI then turn left until joining RDL 202 RMC VOR (TR 022°) bound to RMC VOR. Leave RMC VOR on RDL 032 (TR 032°) until joining RDL 057 OST VOR (TR 057°) bound to OKUNO.

MCA/MCL: OST VOR 5000 FT; DIBVI 6000 FT; LELSU FL 110

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	OST	-	-	-	-	-	+5000	-	Conventional/ RNAV1
TF	XIBRI	Y	187° (190.5)	-	15.0	-	-	-	Conventional/ RNAV1
DF	DIBVI	-	-	-	-	L	+6000	-	Conventional/ RNAV1
TF	RMC	-	022° (024.9)	-	19.0	-	-	-	Conventional/ RNAV1
TF	LELSU	-	032° (035.0)	-	17.1	-	+FL110	-	Conventional/ RNAV1
TF	OKUNO	-	057° (060.6)	-	8.4	-	-	-	Conventional/ RNAV1

**PEPIX 6V**

Proceed on RDL 187 OST VOR via XIBRI – ELVIN (RDL 187/18.9NM OST VOR/DME) until 27 NM OST DME, then turn left until joining RDL 159 TAQ VOR bound to PEPIX.

MCA/MCL: OST VOR/DME 5000 FT; PEPIX FL 100

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	OST	-	-	-	-	-	+5000	-	Conventional/ RNAV1
TF	XIBRI	-	187° (190.5°)	-	15.0	-	-	-	Conventional/ RNAV1
TF	ELVIN	-	187° (190.5°)	-	3.9	-	-	-	Conventional/ RNAV1
TF	ADMOP	-	187° (190.5)	-	10.5	-	-	-	Conventional/ RNAV1
TF	PEPIX	-	159° (162.2°)	-	10.2	-	+FL100	-	Conventional/ RNAV1

**PODOX 6V**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	OST	-	-	-	-	-	+5000	-	RNAV1
TF	XENOL	-	265° (268.1°)	-	30.8	-	-	-	RNAV1
TF	GISPA	-	273° (276.1°)	-	9.5	-	-	-	RNAV1
TF	PODOX	-	307° (309.3°)	-	44.5	-	+FL100	-	RNAV1

**RIFFI 6U**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	RATIR	-	-	-	-	-	+3000	-210	RNAV1
TF	RIFFI	-	169° (172.2°)	-	27.7	-	+FL90	-	RNAV1

**RIFFI 6V**

Proceed on RDL 187 OST VOR via XIBRI (RDL 187/15NM OST VOR/DME) – ELVIN then turn left on TR 131° (RDL 311 PNZ VOR) bound to RIFFI.

MCA/MCL: OST VOR/DME 5000 FT; RIFFI FL 90

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	OST	-	-	-	-	-	+5000	-	Conventional/ RNAV1
TF	XIBRI	-	187° (190.5°)	-	15.0	-	-	-	Conventional/ RNAV1
TF	ELVIN	-	187° (190.5°)	-	3.9	-	-	-	Conventional/ RNAV1
TF	RIFFI	-	131° (133.8°)	-	23.3	-	+FL90	-	Conventional/ RNAV1

**SIPRO 6S**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	OST	-	-	-	-	-	+5000	-	RNAV1
TF	XIBRI	Y	187° (190.5)	-	15.0	-	-	-	RNAV1
DF	DIBVI	-	-	-	-	L	+6000	-	RNAV1
TF	IPMUT	-	022° (024.9)	-	10.0	-	-	-	RNAV1
TF	OTKUB	-	089° (092.5)	-	11.5	-	+FL120	-	RNAV1
TF	FRS	-	089° (092.6)	-	24.0	-	-	-	RNAV1
TF	SIPRO	-	121° (123.8)	-	21.1	-	-	-	RNAV1

**SIPRO 6U**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	RATIR	-	-	-	-	-	+3000	-210	RNAV1
DF	RA501	-	-	-	-	L	+5000	-240	RNAV1
TF	RA502	-	080° (083.5)	-	8.7	-	+FL110	-	RNAV1
TF	FRS	-	097° (100.5)	-	21.1	-	-	-	RNAV1
TF	SIPRO	-	121° (123.8)	-	21.1	-	-	-	RNAV1

**SOVAN 6V**

Proceed on TR 343° (RDL343 OST VOR) bound to SOVAN

MCA/MCL: OST VOR/DME 5000FT; RA531 (RDL343/24NM OST VOR/DME) FL110

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	OST	-	-	-	-	-	+5000	-	Conventional/ RNAV1
TF	RA531	-	343° (346.0°)	-	24.0	-	+FL110	-	Conventional/ RNAV1
TF	SOVAN	-	343° (346.0°)	-	39.7	-	-	-	Conventional/ RNAV1

**TIBER 6S**

Proceed on TR 187° (RDL 187 OST VOR) bound to XIBRI then turn left until joining RDL 202 RMC VOR (TR 022°) bound to RMC VOR. Leave RMC VOR on RDL 358 (TR 358°) bound to TIBER.

MCA/MCL: OST VOR 5000 FT; DIBVI 6000 FT; GEGDU FL110

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	OST	-	-	-	-	-	+5000	-	Conventional/ RNAV1
TF	XIBRI	Y	187° (190.5)	-	15.0	-	-	-	Conventional/ RNAV1
DF	DIBVI	-	-	-	-	L	+6000	-	Conventional/ RNAV1
TF	RMC	-	022° (024.9)	-	19.0	-	-	-	Conventional/ RNAV1
TF	GEGDU	-	358° (001.0)	-	13.0	-	+FL110	-	Conventional/ RNAV1
TF	TIBER	-	358° (001.1)	-	13.5	-	-	-	Conventional/ RNAV1

**PEMAR 6S**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	OST	-	-	-	-	-	+5000	-	RNAV1
TF	XIBRI	Y	187° (190.5)	-	15.0	-	-	-	RNAV1
DF	DIBVI	-	-	-	-	L	+6000	-	RNAV1
TF	RMC	-	022° (024.9)	-	19.0	-	+FL80	-	RNAV1
TF	RA536	-	358° (001.0)	-	8.4	-	-	-	RNAV1
TF	PEMAR	-	068° (070.8)	-	15.5	-	+FL110	-	RNAV1

**WAYPOINT LIST**

<b>Waypoint Identifier</b>	<b>Coordinates</b>
RA501	41°41'38.0" N 012°38'14.7" E
RA502	41°42'28.1" N 012°49'50.0" E
RA531	42°11'31.3" N 012°06'33.1" E
RA536	41°56'41.7" N 012°35'28.3" E