


APP CRS	Rwy Idg	7702
201°	TDZE	578
	Apt Elev	599

RNAV (RNP) Z RWY 20R

NASHVILLE INTL (BNA)

<p>GPS required. Simultaneous approach authorized with Rwy 20L. Use of FD or AP providing RNAV track guidance required during simultaneous operations. For uncompensated Baro-VNAV systems, procedure NA below -11°C (13°F) or above 54°C (130°F). For inoperative MALSf, increase RNP 0.18 all Cats visibility to RVR 5600 and RNP 0.30 all Cats visibility to 1/2.</p>	<p>MALSf</p>	<p>MISSED APPROACH: Climb to 3000 on track 201° to RONLE and hold.</p>
	<p>MALSf</p>	


D-ATIS	NASHVILLE APP CON	NASHVILLE TOWER	GND CON	CLNC DEL	CPDLC
135.1	118.4 360.7	118.6 257.8	121.9 348.6	126.05	




SE-1, 20 MAR 2025 to 17 APR 2025

SE-1, 20 MAR 2025 to 17 APR 2025

ELEV 599	D	TDZE 578
----------	----------	----------



3000	tr 201°	RONLE	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 79).
------	---------	--------------	--



CATEGORY	A	B	C	D
RNP 0.18 DA		927/42	349 (400-7/8)	
RNP 0.30 DA		1042/60	464 (500-1 1/4)	

AUTHORIZATION REQUIRED