

Type of aid MAG VAR Type of supported OPS VOR/ILS/MLS declination	ID	Frequency/ Channel service provider RPI	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Service volume radius GBAS	Remarks
1	2	3	4	5	6	7	8
Dresden							
ILS 22 (CAT III)							
LOC (4° E/2020)	IDRW	109.75 MHz	H24	N 51 07 21.50 E 013 45 06.80		-	Usable: Up to 8.6 NM in the area 035°(L)/026°(R) in relation to RCL MIN interception altitude: 1740 ft MSL. From 8.6 NM to 17 NM in the area 035°(L)/ 026°(R) in relation to RCL MIN interception altitude: 2700 ft MSL. From 17 NM to 22 NM in the area 010°(L)/ 010°(R) in relation to RCL MIN interception altitude: 2700 ft MSL.
GP	-	333.05 MHz	H24	N 51 08 26.92 E 013 46 28.55		-	
DME	IDRW	CH34y (109.75 MHz *)	H24	N 51 08 26.89 E 013 46 28.57	709	-	Operational coverage sector 006°-076°: 25 NM, 10000 ft MSL The DME may only be used for the published approach and departure procedures. * Ghost frequency
LO	FS	374.00 KHz	H24	N 51 11 34.84 E 013 51 00.11		-	Operational range sector 0°-360°: 15 NM 220°, 4.11 NM THR 22
Hermisdorf							
DVOR/DME (3° E/2016)	HDO	108.65 MHz CH23y	H24	N 50 55 41.34 E 014 22 07.68	1433	-	Operational coverage sector 0°-360°: 60 NM, FL 500 The DVOR may only be used for the radials in the published en-route, approach and departure procedures and is not permitted for area navigation. DME unusable in sector 010°-050°: below 0 - 20 NM 4300 ft MSL 20 - 30 NM 6600 ft MSL 30 - 40 NM 9000 ft MSL 40 - 50 NM 11600 ft MSL 50 - 60 NM 14200 ft MSL DME unusable in sector 050°-315°: below 0 - 20 NM 3300 ft MSL 20 - 30 NM 5100 ft MSL 30 - 40 NM 7100 ft MSL 40 - 50 NM 9100 ft MSL 50 - 60 NM 11000 ft MSL DME unusable in sector 315°-010°: below 0 - 20 NM 9700 ft MSL 20 - 30 NM 14700 ft MSL 30 - 40 NM 19800 ft MSL 40 - 50 NM 25100 ft MSL 50 - 60 NM 30000 ft MSL
Wax							
DME	DND	CH101x (115.40 MHz *)	H24	N 51 07 46.21 E 013 45 27.26	761	-	Operational coverage sector 0°-360°: 25 NM, FL 100 DME unusable in sector 345°-275°: below 0 - 10 NM 1800 ft MSL 10 - 20 NM 3100 ft MSL 20 - 25 NM 3800 ft MSL Unusable in sector 275°-345° below 7500 ft MSL. DME usable for arrival, approach and departure procedures. * Ghost frequency