

INITIAL CLIMB RWY32 description

After take-off proceed on TR 312° until PO601, then turn left to join the assigned SID.

Minimum climb gradient:

- 300 ft/NM (4.9%) until passing 6000 ft due to obstacles;
- 365 ft/NM (6.0%) until passing FL90 for ATC reasons.

Execute the turn with:

- 20° minimum bank angle;
- IAS MAX 220 KT

SID RNAV 1 RWY 32 CAT D (CAT A-B-C ATC Discretion) description

Initial climb procedure executed:

AVCUP 6A (ATC Discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO601	Y	312°	3 E	-	-	+1100	- 220	RNAV1
DF	PO603	-	-	-	-	L	+6000	- 220	RNAV1
TF	AVCUP	-	136°	-	40.9	-	+FL130	-	RNAV1

EXFIN 7A

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO601	Y	312°	3 E	-	-	+1100	- 220	RNAV1
DF	PO603	-	-	-	-	L	+6000	- 220	RNAV1
TF	PO607		061°	-	17.5	-	+FL110	- 220	RNAV1
TF	EXFIN	-	061°	-	9	-	-	-	RNAV1

ETHEZ 6A (ATC Discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO601	Y	312°	3 E	-	-	+1100	- 220	RNAV1
DF	PO603	-	-	-	-	L	+6000	- 220	RNAV1
TF	ETHEZ	-	115°	-	39.3	-	+FL95	-	RNAV1

OSBUL 7V

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO601	Y	312°	3 E	-	-	+1100	- 220	RNAV1
DF	PO603	-	-	-	-	L	+6000	- 220	RNAV1
TF	OSBUL	-	184°	-	28.6	-	+FL90	- 220	RNAV1

OSKOR 7V

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO601	Y	312°	3 E	-	-	+1100	- 220	RNAV1
DF	PO603	-	-	-	-	L	+6000	- 220	RNAV1
TF	PO604	-	261°	-	15.5	R	-	- 220	RNAV1
TF	OSKOR	-	007°	-	23.4	R	+FL110	- 220	RNAV1

UGHAD 6A

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO601	Y	312°	3 E	-	-	+1100	- 220	RNAV1
DF	PO603	-	-	-	-	L	+6000	- 220	RNAV1
TF	UGHAD	-	095°	-	36.5	-	+FL95	-	RNAV1

UVNIB 1V (ATC Discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CF	PO601	Y	312°	3 E	-	-	+1100	- 220	RNAV1
DF	PO603	-	-	-	-	L	+6000	- 220	RNAV1
TF	PO604	-	261°	-	15.5	-	-	- 220	RNAV1
TF	UVNIB	-	261°	-	20.3	-	+FL90	-	RNAV1

Waypoints Table formatted according ARINC 424 standards

Waypoint	Latitude	Longitude
PO601	N45274437	E010170028
PO603	N45174094	E010224682
PO604	N45155688	E010005760
PO607	N45251423	E010451046