

HOF-PLAUEN
RWY 08/26

STANDARD ARRIVAL ROUTES - INSTRUMENT (STAR)
TABULAR DESCRIPTION
RNAV (GPS)

General Remarks	
1.	IFR PROFILES WITHIN AIRSPACE CLASS E. WATCH OUT FOR VFR TRAFFIC UNKNOWN TO ATC.
2.	1. RNAV-1 or RNP-1 or A-RNP equivalent 2. GPS required 3. DME/DME, DME/DME/IRU not authorized

ABERU 1B
ABERU ONE BRAVO

Procedure Remarks / Procedure Timesheet
-

Recommended Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) / Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	NAV Specification	Remarks
IF	ABERU	N 50 04 09.10 E 012 05 37.39	-	-	-	-	A6000+	-	-	refer to chart	-
TF	QM001	N 50 07 52.79 E 011 59 53.98	-	(T 315.3) 313	5.2	-	A6000+	-	-	refer to chart	-
TF	HOF	N 50 17 04.66 E 011 45 41.02	-	(T 315.1) 313	13.0	-	A5000+	-	-0.73	refer to chart	-

KULOK 1B
KULOK ONE BRAVO

Procedure Remarks / Procedure Timesheet
-

Recommended Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) / Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	NAV Specification	Remarks
IF	KULOK	N 50 04 22.09 E 011 37 49.67	-	-	-	-	A4000+	-	-	refer to chart	-
TF	HOF	N 50 17 04.66 E 011 45 41.02	-	(T 021.7) 019	13.7	-	A4000+	-	-	refer to chart	-

TABAT 1B
TABAT ONE BRAVO

Procedure Remarks / Procedure Timesheet
-

Recommended Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) / Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	NAV Specification	Remarks
IF	TABAT	N 50 33 30.51 E 011 31 52.50	-	-	-	-	A6000+	-	-	refer to chart	-
TF	QM002	N 50 27 47.55 E 011 36 42.05	-	(T 151.7) 149	6.5	-	A6000+	-	-	refer to chart	-
TF	HOF	N 50 17 04.66 E 011 45 41.02	-	(T 151.9) 149	12.2	-	A5000+	-	-0.77	refer to chart	-

RNAV HOLDING IDENTIFICATION

Recommended Path Terminator	Holding Fix	Coordinates	Inbound (True Track°) / MAG Track°	Max Speed (kt IAS)	Altitude (ft) / Flight Level	Time / Distance outbound	Turn Direction	Remarks
HM	HOF	N 50 17 04.66 E 011 45 41.02	(T 176.8) 174	230-	A3800+	1 min	R	-