



RNAV STAR RWY 08

EMPOM 4D EXUPA 4D IPMOT 4D NIRPU 4D OTKIL 4D UPAPU 4D UVOPA 3D

DME/DME OPS: NOT SUPPORTED

RCF: SELECT TRANSPONDER CODE 7600

ROUTES: RNAV PROC CODING ON THE VERSO OF THE CHART
ATC WILL GIVE DESCENT CLEARANCES

RNAV STAR HAS BEEN GIVEN AND ACKNOWLEDGED:
FOLLOW THE STAR TO THE RESPECTIVE RWY AND
EXECUTE IAP AND LAND

WPT CONSTRAINTS: ALT / FL / SPEED CONSTRAINTS MUST ALWAYS BE FOLLOWED AS
PUBLISHED UNLESS EXPLICITLY CANCELLED BY ATC

DURING RADAR VECTORING BEFORE IAF:
IN ACCORDANCE WITH THE RULES OF THE AIR

CD OPS: BY ATC CLR IF TFC PERMITS. PLAN CD PATH ACCORDING TO STAR

AREA MNM ALT: SEE AMA INDEX, AIP ENR 6.1 - 3

NOISE ABATEMENT: AVOID OVERFLYING THE CITY OF TURKU BELOW 2000

CHG: MAG VAR

EFTU RNAV STAR RWY 08										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Constraints		
			ID	Flyover				LVL	LVL	Speed
EMPOM 4D RNAV 1	010	IF	EMPOM	-	-	-	-	F070+		
	020	TF	AMDIK	-	017°	026.9°T	13.5	A2200+		K240-
	030	TF	PIGES	-	345°	354.5°T	5.0	A2200+		
EXUPA 4D RNAV 1	010	IF	EXUPA	-	-	-	-	F070+		
	020	TF	RETPU	-	267°	276.5°T	24.9			
	030	TF	AMDIK	-	255°	264.9°T	10.8	A2200+		K240-
	040	TF	PIGES	-	345°	354.5°T	5.0	A2200+		
IPMOT 4D RNAV 1	010	IF	IPMOT	-	-	-	-	F070+		
	020	TF	TAVSU	-	291°	300.0°T	19.3			
	030	TF	PIVED	-	256°	265.2°T	10.8			
	040	TF	LOMTU	-	255°	264.8°T	10.8	A2200+		K240-
	050	TF	PIGES	-	165°	174.5°T	5.0	A2200+		
NIRPU 4D RNAV 1	010	IF	NIRPU	-	-	-	-	F100+		
	020	TF	LOMTU	-	203°	212.3°T	13.8	A2200+		K240-
	030	TF	PIGES	-	165°	174.5°T	5.0	A2200+		
OTKIL 4D RNAV 1	010	IF	OTKIL	-	-	-	-	F070+		
	020	TF	PIGES	-	075°	084.9°T	15.9	A2200+		
UPAPU 4D RNAV 1	010	IF	UPAPU	-	-	-	-	F070+		
	020	TF	AMDIK	-	297°	306.1°T	23.6	A2200+		K240-
	030	TF	PIGES	-	345°	354.5°T	5.0	A2200+		
UVOPA 3D RNAV 1	010	IF	UVOPA	-	-	-	-	F100+		
	020	TF	LOMTU	-	225°	234.7°T	20.0	A2200+		K240-
	030	TF	PIGES	-	165°	174.5°T	5.0	A2200+		

RNAV Holdings							
ID	INBD TR	INBD MAG	Turn Direction	Speed	MNM HLDG LVL	TIME	DIST NM
PIGES	084.8°T	075°	Right	K230-	A2200	1 MIN	-

WPT COORD
SEE PAGE EFTU AD 2.15 - 1